

Deka ordnance batteries outrank the ordinary with power and reliability.

- Specially designed to meet military specifications. Certificate of compliance available on request.
- Available wet or dry.
- Up to 750 CCA and 230 min. reserve capacity
- Maintenance-free types feature calcium grids with microporous polyethylene envelope separators and double glass-mat insulation.
- Screw-in vents are submersible to 4-feet underwater and make battery maintainable in case of accidental overcharging.
- Full-frame, heavy-duty plates, high density oxide and pure, demineralized electrolyte prevent internal shorts and withstand high cycling service for longest battery life.
- Durable ribbed polypropylene case provides protection in abusive applications.
- Special leak resistant cover keeps battery compartments clean and dry up to a 45° tilt.
- Anchor lock elements resist vibration damage for longer service life.
- Includes handles for ease of transportation and installation.
- Over 250 quality control checks assure reliability and long service life.
- Made in the U.S.A.... Your assurance of quality.

	RECYCLE
	QUALITY SYSTEM CERTIFIED
_	ISO 9001
IS	O/TS 16949

S AY

ENVIRONMENTAL SYSTEM CERTIFIED ISO 14001

GROUP NO.	ТҮРЕ	FOOTNOTES	PERFORMANCE LEVEL				QTS.	APPROXIMATE WEIGHT		MAXIMUM OVERALL DIMENSIONS (in inches and mm)			
	NO.		CCA @ 0°F	RESERVE Capacity	20 AH Rate	VOLTS	OF ACID	WET	DRY	L	W	,	н
	ORDNANCE												
2HN	2HND	12,21,25,32	400	75	45	12	2.9		25.0	10½ 260	5¼ 133	9	229
4HN	4HND	11,17,21,25,32	235	28	21	24	2.9		27.5	10½ 260	5¼ 133	9	229
6TL	6TMF	6,17,21,25,30	750	230	120	12	7.6	73.0	52.0	11½ 286	10½ 267	9	229

FOOTNOTES:

- 6 Black cover / Brown case
- 11- Low maintenance-low antimony grids
- 12-Hybrid construction
- 17- Includes handle

- 21 Anchor lock elements
- **25** With individual vent caps
- **30** Available dry-add "D" suffix to part number **32** Available dry charged only
- 32- Available dry charged

- All batteries manufactured in polypropylene cases except where noted.

- Maintenance-free batteries have microporous, polyethylene envelope separators.

EAST PENN manufacturing co., inc.

DISTRIBUTED BY:

UNANO S

Lyon Station, PA 19536-0147 • Phone: 610-682-6361 • Fax: 610-682-4781 Order Department Hotline: 610-682-4231 www.dekabatteries.com