



INDUSTRIAL BATTERIES

CROWN

WALKIE, RIDER/WALKIE, TOW TRACTORS

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity 6 Hr. Rate		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.	
			KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)		
GPW See Note A 25.625 x 8.875 x 24	24	12-D85-5	3.96	170	85	3167	24.25	8.3125	23.1875	464	X		A	21	SB 6325	w/945
	24	12-H80-5	3.72	160	80	3167	24.25	8.3125	23.1875	445	X		A	21	SB 6325	w/945
	24	12-P95-5	4.42	190	95	3167	24.25	8.3125	23.1875	469	X		A	21	SB 6325	w/945
	24	12-D85-7	5.94	255	85	3042	25.25	8.5625	23.1875	567	X		A	21	SB 6325	w/945
	24	12-H80-7	5.59	240	80	3042	25.25	8.5625	23.1875	544	X		A	21	SB 6325	w/945
	24	12-P95-7	6.63	285	95	3042	25.25	8.5625	23.1875	573	X		A	21	SB 6325	w/945
15WB, 20W, 20WR, 30W 30WA, 40W 35.0625 x 6.625 x 23.25	24	12-D85-5	3.96	170	85	3301	33.0625	6.4375	22.75	496		X	See Note B		SB 6325	w/945
	24	12-D85-5	3.96	170	85	3068	24.75	6.4375	22.5625	412	X		See Note B		SB 6325	w/945
	24	12-H80-5	3.72	160	80	3301	33.0625	6.4375	22.75	476	X		See Note B		SB 6325	w/945
	24	12-H80-5	3.72	160	80	3068	24.75	6.4375	22.5625	396	X		See Note B		SB 6325	w/945
	24	12-P95-5	4.42	190	95	3301	33.0625	6.4375	22.75	501	X		See Note B		SB 6325	w/945
	24	12-P95-5	4.42	190	95	3068	24.75	6.4375	22.5625	416	X		See Note B		SB 6325	w/945
	24	12-D85-7	5.94	255	85	3079	33.5625	6.4375	22.5625	567	X		See Note B		SB 6325	w/945
	24	12-H80-7	5.59	240	80	3079	33.5625	6.4375	22.5625	544	X		See Note B		SB 6325	w/945
20W, 20WB, 20WR, 25WB 30W, 30WA, 30WB, 30WR 40W, 40WB 31.75 x 13.125 x 23.25	24	12-D85-11	9.89	425	85	3041	26.0625	12.75	22.625	869		X	See Note B		SB 6325	w/945
	24	12-H80-11	9.31	400	80	3041	26.0625	12.75	22.625	834	X		See Note B		SB 6325	w/945
	24	12-P95-11	11.06	475	95	3041	26.0625	12.75	22.625	878	X		See Note B		SB 6325	w/945
	24	12-D85-13	11.87	510	85	3082	30.5625	12.75	22.625	1025	X		See Note B		SB 6325	w/945
	24	12-H80-13	11.17	480	80	3082	30.5625	12.75	22.625	984	X		See Note B		SB 6325	w/945
	24	12-P95-13	13.27	570	95	3082	30.5625	12.75	22.625	1035	X		See Note B		SB 6325	w/945
PE, PW 30.875 x 7.875 x 23.25	12	6-D85-13	5.94	510	85	1088	30.5	7.75	23.1875	538	X		A	20	SB 6325	w/945
	12	6-H80-13	5.59	480	80	1088	30.5	7.75	23.1875	516	X		A	20	SB 6325	w/945
	12	6-P95-13	6.63	570	95	1088	30.5	7.75	23.1875	543	X		A	20	SB 6325	w/945

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE, RIDER/WALKIE, TOW TRACTORS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length Pos. (in.)		Standard Conn.	
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No				
PC, PE, PR, PW, TR, TW TWR 35.0625 x 6.625 x Open	24	12-D85-5	3.96	170	85	3081	24.625	6.4375	23.1875	418	X		See Note B	SB 6325	w/945	
	24	12-H80-5	3.72	160	80	3081	24.625	6.4375	23.1875	401	X		See Note B	SB 6325	w/945	
	24	12-P95-5	4.42	190	95	3081	24.625	6.4375	23.1875	422	X		See Note B	SB 6325	w/945	
	24	12-D85-7	5.94	255	85	3022	33.5625	6.4375	23.1875	574	X		See Note B	SB 6325	w/945	
	24	12-H80-7	5.59	240	80	3022	33.5625	6.4375	23.1875	551	X		See Note B	SB 6325	w/945	
	24	12-P95-7	6.63	285	95	3022	33.5625	6.4375	23.1875	580	X		See Note B	SB 6325	w/945	
PC, PE, PR, PW, TR, TW TWR 31.75 x 13.125 x Open	24	12-D85-11	9.89	425	85	3020	26.0625	12.75	23.25	883	X		See Note B	SB 6325	w/945	
	24	12-H80-11	9.31	400	80	3020	26.0625	12.75	23.25	848	X		See Note B	SB 6325	w/945	
	24	12-P95-11	11.06	475	95	3020	26.0625	12.75	23.25	892	X		See Note B	SB 6325	w/945	
	24	12-D85-13	11.87	510	85	3019	30.5625	12.75	23.25	1049	X		See Note B	SB 6325	w/945	
	24	12-H80-13	11.17	480	80	3019	30.5625	12.75	23.25	1007	X		See Note B	SB 6325	w/945	
	24	12-P95-13	13.27	570	95	3019	30.5625	12.75	23.25	1059	X		See Note B	SB 6325	w/945	
WE 2000, WS 2000 32.5 x 8.625 x 24.625 Min. Battery Wt. - 644 lbs.	24	12-D85-7	cm	5.94	255	85	3706	32	8.5625	23.1875	680	X		A, B	18	SB 6325
	24	12-H80-7	cm	5.59	240	80	3706	32	8.5625	23.1875	653	X		A, B	18	SB 6325
	24	12-P95-7	cm	6.63	285	95	3706	32	8.5625	23.1875	687	X		A, B	18	SB 6325
	24	12-D85-7		5.94	255	85	3654	27.5625	8.5625	22.5625	660		X	AB	18	SB 6325
	24	12-H80-7		5.59	240	80	3654	27.5625	8.5625	22.5625	634		X	AB	18	SB 6325
	24	12-P95-7		6.63	285	95	3654	27.5625	8.5625	22.5625	667		X	AB	18	SB 6325
WP2030, WP2035, WP2330 WP2335 25.8125 x 7.9375 x 26	24	(4) 8GGC2	pm	3.60	155		3801	25.5	7.5	24.5	340	X		A	26	SB 6325
	24	12-D85-5		3.96	170	85	3081	24.625	6.4375	23.1875	418	X		A	20	SB 6325
	24	12-H80-5		3.72	160	80	3081	24.625	6.4375	23.1875	401	X		A	20	SB 6325
	24	12-P95-5		4.42	190	95	3081	24.625	6.4375	23.1875	422	X		A	20	SB 6325
WP2040, WP2045, WP2340 WP2345 25.8125 x 9.125 x 26	24	(4) 8GGC2	pm	3.60	155		3800	25.5	8.5625	24.5	340	X		A	26	SB 6325
	24	12-D85-7		5.94	255	85	3042	25.25	8.5625	23.1875	567	X		A	20	SB 6325
	24	12-H80-7		5.59	240	80	3042	25.25	8.5625	23.1875	544	X		A	20	SB 6325
	24	12-P95-7		6.63	285	95	3042	25.25	8.5625	23.1875	573	X		A	20	SB 6325

* Note: Consult Factory for Special Battery and Pricing For Weight Variance.

Note A: GPW requires cable cut out in cover.

Note B: W, WA, WB, WR, A-18"; TW, TWR, TR without SCR Control, B-12"; TW, TWR, TR with SCR Control, A-12"; PW, PE, PC, PR, A-20".

cm - Charge-Mate includes on-board charger

pm - Powr-Mate includes on-board charger.

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

STOCK PICKERS

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity 6 Hr. Rate		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
15SP48, 30SP42, 30SP48	24	12-D160-11	18.62	800	160	3025	35.0625	13.1875	30.5	1647		X	A	21	SB 6322
SP3010-30, SP3015-30	24	12-D125-15	20.37	875	125	3036	35.0625	12.875	30.5	1651		X	A	21	SB 6322
SP3020-30, SP3040-30	24	12-H120-15	19.56	840	120	3036	35.0625	12.875	30.5	1634		X	A	21	SB 6322
SP3210-30, SP3220-30	24	12-P140-15	22.81	980	140	3036	35.0625	12.875	30.5	1668		X	A	21	SB 6322
SP3250H-30, SP3410-30 SP3420-30, SP3450H-30 36.25 x 14.25 x 31															
30SP36	24	12-D85-13	11.87	510	85	3082	30.5625	12.75	22.625	1025		X	A	18	SB 6325 w/945
31.75 x 13.125 x 23.25	24	12-H80-13	11.17	480	80	3082	30.5625	12.75	22.625	984		X	A	18	SB 6325 w/945
	24	12-P95-13	13.27	570	95	3082	30.5625	12.75	22.625	1035		X	A	18	SB 6325 w/945
SP3205-30	24	12-D85-13	11.87	510	85	3082	30.5625	12.75	22.625	1025		X	A	21	SB 6322
31.75 x 13.125 x 23.25	24	12-H80-13	11.17	480	80	3082	30.5625	12.75	22.625	984		X	A	21	SB 6322
	24	12-P95-13	13.27	570	95	3082	30.5625	12.75	22.625	1035		X	A	21	SB 6322
SP3405-30	24	12-D85-13	11.87	510	85	3019	30.5625	12.75	23.25	1049	X		A	21	SB 6325
31.75 x 13.125 x 23.25	24	12-H80-13	11.17	480	80	3019	30.5625	12.75	23.25	1007	X		A	21	SB 6325
	24	12-P95-13	13.27	570	95	3019	30.5625	12.75	23.25	1059	X		A	21	SB 6325

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

SLIP SHEET RIDER

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity 6 Hr. Rate		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
SSR	24	12-D160-9	14.90	640	160	3007	35.062	10.937	31.125	1417	X		A	12	SB 6322
36.375 x 11.75 x Open	24	12-D125-11	14.55	625	125	3013	31.875	10.8125	31.125	1247	X		A	12	SB 6322
	24	12-H120-11	13.97	600	120	3013	31.875	10.8125	31.125	1235	X		A	12	SB 6322
	24	12-P140-11	16.30	700	140	3013	31.875	10.8125	31.125	1259	X		A	12	SB 6322
	24	12-D125-13	17.46	750	125	3179	35.5625	11.5625	31.125	1475	X		A	12	SB 6322
	24	12-H120-13	16.76	720	120	3179	35.5625	11.5625	31.125	1460	X		A	12	SB 6322
	24	12-P140-13	19.56	840	140	3179	35.5625	11.5625	31.125	1490	X		A	12	SB 6322

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

REACH, STRADDLE TRUCKS

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	Length (in.)	
25RR, 30RS, 35RR, 40RS RR-3000-35, RS-3000-40 RS3510-40, RS3520-40 38.375 x 12.1875 x 31	24	12-D160-9	14.90	640	160	3511	35.0625	10.9375	30.5	1309		X	A	9	SB 6322
	24	12-D125-11	14.55	625	125	3014	31.875	10.8125	30.5	1244		X	A	9	SB 6322
	24	12-H120-11	13.97	600	120	3014	31.875	10.8125	30.5	1232		X	A	9	SB 6322
	24	12-P140-11	16.30	700	140	3014	31.875	10.8125	30.5	1256		X	A	9	SB 6322
	24	12-D125-13	17.46	750	125	3176	35.5625	11.5625	30.5	1457		X	A	9	SB 6322
	24	12-H120-13	16.76	720	120	3176	35.5625	11.5625	30.5	1442		X	A	9	SB 6322
	24	12-P140-13	19.56	840	140	3176	35.5625	11.5625	30.5	1472		X	A	9	SB 6322
	36	18-D125-9	17.46	500	125	6063	37.6875	10.9375	30.5	1495		X	A	9	SB 6322
	36	18-H120-9	16.76	480	120	6063	37.6875	10.9375	30.5	1480		X	A	9	SB 6322
	36	18-P140-9	19.56	560	140	6063	37.6875	10.9375	30.5	1510		X	A	9	SB 6322
25RR, 30RS, 35RR, 40RS RR-3000-35, RR-3000-40 RS-3000-40, RS3510-40 38.375 x 14.25 x 31	24	12-D160-11	18.62	800	160	3025	35.0625	13.1875	30.5	1647		X	A	9	SB 6322
	24	12-D125-13	17.46	750	125	3093	30.5625	12.75	30.5	1444		X	A	9	SB 6322
	24	12-H120-13	16.76	720	120	3093	30.5625	12.75	30.5	1430		X	A	9	SB 6322
	24	12-P140-13	19.56	840	140	3093	30.5625	12.75	30.5	1458		X	A	9	SB 6322
	24	12-D125-15	20.37	875	125	3036	35.0625	12.875	30.5	1651		X	A	9	SB 6322
	24	12-H120-15	19.56	840	120	3036	35.0625	12.875	30.5	1634		X	A	9	SB 6322
	24	12-P140-15	22.81	980	140	3036	35.0625	12.875	30.5	1668		X	A	9	SB 6322
	24	12-D125-17	23.28	1000	125	3127	38.1875	13.5	30.5625	1944		X	A	9	SB 6322
	24	12-H120-17	22.35	960	120	3127	38.1875	13.5	30.5625	1925		X	A	9	SB 6322
	24	12-P140-17	26.07	1120	140	3127	38.1875	13.5	30.5625	1963		X	A	9	SB 6322
24RR, 25RD, 30RD, 30RS 35RD, 35RR, 40RS, 45RR 50RS, RD 3000-30 RS3520-40 38.375 x 14.25 x 31	36	18-D125-11	21.83	625	125	6016	37.8125	13.3125	30.5625	1852		X	A	9	SB 6320
	36	18-H120-11	20.95	600	120	6016	37.8125	13.3125	30.5625	1833		X	A	9	SB 6320
	36	18-P140-11	24.44	700	140	6016	37.8125	13.3125	30.5625	1871		X	A	9	SB 6320
25RR, 30RS, 35RR, 40RS RR-3000-40, RR3000-35 RS-3000-40, RS3510-40 38.375 x 16.25 x 31	24	12-D160-13	22.35	960	160	3049	35.25	15.5625	30.5625	1985		X	A	9	SB 6322
	24	12-D125-17	23.28	1000	125	3127	38.1875	13.5	30.5625	1944		X	A	9	SB 6322
	24	12-H120-17	22.35	960	120	3127	38.1875	13.5	30.5625	1925		X	A	9	SB 6322
	24	12-P140-17	26.07	1120	140	3127	38.1875	13.5	30.5625	1963		X	A	9	SB 6322
	24	12-D125-19	26.19	1125	125	3134	38.1875	15	30.5625	2126		X	A	9	SB 6322
	24	12-H120-19	25.14	1080	120	3134	38.1875	15	30.5625	2105		X	A	9	SB 6322
	24	12-P140-19	29.33	1260	140	3134	38.1875	15	30.5625	2147		X	A	9	SB 6322

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

REACH, STRADDLE TRUCKS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity 6 Hr. Rate		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
25RD, 25RR, 30RD, 30RS	36	18-D125-13	26.19	750	125	6005	37.8125	15.5625	30.5625	2166		X	A	9	SB 6320
35RD, 35RR, 40RS, 45RR	36	18-H120-13	25.14	720	120	6005	37.8125	15.5625	30.5625	2144		X	A	9	SB 6320
50RS, RD-3000-30	36	18-P140-13	29.33	840	140	6005	37.8125	15.5625	30.5625	2188		X	A	9	SB 6320
RR-3000-45, RS-3000-40 RS3520-40 38.375 x 16.25 x 31															
30RD, 45RR, RD-3000-30	36	18-D125-15	30.56	875	125	6045	38.1875	17.8125	30.5625	2486		X	A	9	SB 6320
RR-3000-45	36	18-H120-15	29.33	840	120	6045	38.1875	17.8125	30.5625	2461		X	A	9	SB 6320
38.5625 x 18 x 31	36	18-P140-15	34.22	980	140	6045	38.1875	17.8125	30.5625	2511		X	A	9	SB 6320
38.5625 x 20.75 x 31	36	18-D125-17	34.92	1000	125	6069	38.1875	20.0625	30.5625	2836		X	A	9	SB 6320
	36	18-H120-17	33.52	960	120	6069	38.1875	20.0625	30.5625	2808		X	A	9	SB 6320
	36	18-P140-17	39.11	1120	140	6069	38.1875	20.0625	30.5625	2864		X	A	9	SB 6320
RR5010-35	24	12-D160-9	14.90	640	160	3511	35.0625	10.9375	30.5	1309		X	D-Rear	18	SB 6322
38.375 x 12.1875 x 31	24	12-D125-13	17.46	750	125	3176	35.5625	11.5625	30.5	1457		X	D-Rear	18	SB 6322
Min. Battery Wt. - 1300 lbs.	24	12-H120-13	16.76	720	120	3176	35.5625	11.5625	30.5	1442		X	D-Rear	18	SB 6322
	24	12-P140-13	19.56	840	140	3176	35.5625	11.5625	30.5	1472		X	D-Rear	18	SB 6322
	24	12-D125-15	20.37	875	125	3115	38.0625	11.875	30.5	1677		X	D-Rear	18	SB 6322
	24	12-H120-15	19.56	840	120	3115	38.0625	11.875	30.5	1660		X	D-Rear	18	SB 6322
	24	12-P140-15	22.81	980	140	3115	38.0625	11.875	30.5	1694		X	D-Rear	18	SB 6322
RR5010-35, RR5010-40	24	12-D160-11	18.62	800	160	3025	35.0625	13.1875	30.5	1647		X	D-Rear	18	SB 6322
38.375 x 14.25 x 31	24	12-D125-15	20.37	875	125	3036	35.0625	12.875	30.5	1651		X	D-Rear	18	SB 6322
Min. Battery Wt. - 1600 lbs.	24	12-H120-15	19.56	840	120	3036	35.0625	12.875	30.5	1634		X	D-Rear	18	SB 6322
	24	12-P140-15	22.81	980	140	3036	35.0625	12.875	30.5	1668		X	D-Rear	18	SB 6322
	24	12-D125-17	23.28	1000	125	3127	38.1875	13.5	30.5625	1944		X	D-Rear	18	SB 6322
	24	12-H120-17	22.35	960	120	3127	38.1875	13.5	30.5625	1925		X	D-Rear	18	SB 6322
	24	12-P140-17	26.07	1120	140	3127	38.1875	13.5	30.5625	1963		X	D-Rear	18	SB 6322
RR5010-35, RR5010-40	24	12-D160-13	22.35	960	160	3049	35.25	15.5625	30.5625	1985		X	D-Rear	18	SB 6322
38.375 x 16.25 x 31	24	12-D125-17	23.28	1000	125	3127	38.1875	13.5	30.5625	1944		X	D-Rear	18	SB 6322
Min. Battery Wt. - 1880 lbs.	24	12-H120-17	22.35	960	120	3127	38.1875	13.5	30.5625	1925		X	D-Rear	18	SB 6322
	24	12-P140-17	26.07	1120	140	3127	38.1875	13.5	30.5625	1963		X	D-Rear	18	SB 6322
	24	12-D125-19	26.19	1125	125	3134	38.1875	15	30.5625	2126		X	D-Rear	18	SB 6322
	24	12-H120-19	25.14	1080	120	3134	38.1875	15	30.5625	2105		X	D-Rear	18	SB 6322
	24	12-P140-19	29.33	1260	140	3134	38.1875	15	30.5625	2147		X	D-Rear	18	SB 6322

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

REACH, STRADDLE TRUCKS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos. (in.)	(in.)	
RR5020-35	36	18-D125-9	17.46	500	125	6063	37.6875	10.9375	30.5	1495		X	D-Rear	18	SB 6320
38.375 x 12.1875 x 31	36	18-H120-9	16.76	480	120	6063	37.6875	10.9375	30.5	1480		X	D-Rear	18	SB 6320
Min. Battery Wt. - 1300 lbs.	36	18-P140-9	19.56	560	140	6063	37.6875	10.9375	30.5	1510		X	D-Rear	18	SB 6320
RR5020-35, RD5020-30	36	18-D125-11	21.83	625	125	6016	37.8125	13.3125	30.5625	1852		X	D-Rear	18	SB 6320
38.375 x 14.25 x 31	36	18-H120-11	20.95	600	120	6016	37.8125	13.3125	30.5625	1833		X	D-Rear	18	SB 6320
Min. Battery Wt. - 1600 lbs.	36	18-P140-11	24.44	700	140	6016	37.8125	13.3125	30.5625	1871		X	D-Rear	18	SB 6320
RR5020-35, RD5020-30	36	18-D125-13	26.19	750	125	6005	37.8125	15.5625	30.5625	2166		X	D-Rear	18	SB 6320
RD5060S-30, RD5080S-30	36	18-H120-13	25.14	720	120	6005	37.8125	15.5625	30.5625	2144		X	D-Rear	18	SB 6320
RR5020-45, RR5060S-45	36	18-P140-13	29.33	840	140	6005	37.8125	15.5625	30.5625	2188		X	D-Rear	18	SB 6320
RR5080S-45															
38.375 x 16.25 x 31															
Min. Battery Wt. - 2000 lbs.															
RR5020-45, RD5020-30	36	18-D125-15	30.56	875	125	6045	38.1875	17.8125	30.5625	2486		X	D-Rear	18	SB 6320
38.6875 x 18 x 31	36	18-H120-15	29.33	840	120	6045	38.1875	17.8125	30.5625	2461		X	D-Rear	18	SB 6320
Min. Battery Wt. - 2280 lbs.	36	18-P140-15	34.22	980	140	6045	38.1875	17.8125	30.5625	2511		X	D-Rear	18	SB 6320
RR5020-45, RD5020-30	36	18-D125-17	34.92	1000	125	6069	38.1875	20.0625	30.5625	2836		X	D-Rear	21	SB 6320
RD5060S-30, RD5080S-30	36	18-H120-17	33.52	960	120	6069	38.1875	20.0625	30.5625	2808		X	D-Rear	21	SB 6320
RR5060S-45, RR5080S-45	36	18-P140-17	39.11	1120	140	6069	38.1875	20.0625	30.5625	2864		X	D-Rear	21	SB 6320
38.6875 x 20.75 x 31															
Min. Battery Wt. - 2600 lbs.															

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

STAND-UP RIDERS

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos. (in.)	(in.)	
RC25	36	18-D125-9	17.46	500	125	6063	37.6875	10.9375	30.5	1495		X	A	9	SB 6320
38.5625 x 11.4375 x 31	36	18-H120-9	16.76	480	120	6063	37.6875	10.9375	30.5	1480		X	A	9	SB 6320
	36	18-P140-9	19.56	560	140	6063	37.6875	10.9375	30.5	1510		X	A	9	SB 6320

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are $\pm 1/16"$. Battery weights may vary $\pm 5\%$. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

STAND-UP RIDERS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
RC25, RC30, RC3020-30 38.5625 x 13.6875 x 31	36	18-D125-11	21.83	625	125	6016	37.8125	13.3125	30.5625	1852		X	A	9	SB 6320
	36	18-H120-11	20.95	600	120	6016	37.8125	13.3125	30.5625	1833		X	A	9	SB 6320
	36	18-P140-11	24.44	700	140	6016	37.8125	13.3125	30.5625	1871		X	A	9	SB 6320
RC30, RC3020-30 38.5625 x 15.875 x 31	36	18-D125-13	26.19	750	125	6005	37.8125	15.5625	30.5625	2166		X	A	9	SB 6320
	36	18-H120-13	25.14	720	120	6005	37.8125	15.5625	30.5625	2144		X	A	9	SB 6320
	36	18-P140-13	29.33	840	140	6005	37.8125	15.5625	30.5625	2188		X	A	9	SB 6320
RC30, RC3020-35, RC35 38.5625 x 18.375 x 31	36	18-D125-15	30.56	875	125	6045	38.1875	17.8125	30.5625	2486		X	A	9	SB 6320
	36	18-H120-15	29.33	840	120	6045	38.1875	17.8125	30.5625	2461		X	A	9	SB 6320
	36	18-P140-15	34.22	980	140	6045	38.1875	17.8125	30.5625	2511		X	A	9	SB 6320
RC3020-40, RC40 38.5625 x 20.75 x 31	36	18-D125-17	34.92	1000	125	6069	38.1875	20.0625	30.5625	2836		X	A	9	SB 6320
	36	18-H120-17	33.52	960	120	6069	38.1875	20.0625	30.5625	2808		X	A	9	SB 6320
	36	18-P140-17	39.11	1120	140	6069	38.1875	20.0625	30.5625	2864		X	A	9	SB 6320

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

THREE WHEEL SIT-DOWN RIDERS

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
SC25 38.625 x 15.875 x 23.125	36	18-D85-13	17.81	510	85	6062	37.6875	15.4375	22.625	1507		X	A	9	SB 6320
	36	18-H80-13	16.76	480	80	6062	37.6875	15.4375	22.625	1447		X	A	9	SB 6320
	36	18-P95-13	19.90	570	95	6062	37.6875	15.4375	22.625	1522		X	A	9	SB 6320
SC25 38.625 x 18.375 x 23.125	36	18-D85-15	20.78	595	85	6002	38.1875	17.8125	22.6875	1773		X	A	9	SB 6320
	36	18-H80-15	19.56	560	80	6002	38.1875	17.8125	22.6875	1702		X	A	9	SB 6320
	36	18-P95-15	23.22	665	95	6002	38.1875	17.8125	22.6875	1791		X	A	9	SB 6320
SC30 38.5625 x 20.625 x 23.125	36	18-D85-17	23.75	680	85	6015	38.1875	20.0625	22.6875	2045		X	A	9	SB 6320
	36	18-H80-17	22.35	640	80	6015	38.1875	20.0625	22.6875	1963		X	A	9	SB 6320
	36	18-P95-17	26.54	760	95	6015	38.1875	20.0625	22.6875	2065		X	A	9	SB 6320
SC30, SC35 38.5625 x 22.8125 x 23.125	36	18-D85-19	26.71	765	85	6041	38.1875	22.3125	22.6875	2242		X	A	9	SB 6320
	36	18-H80-19	25.14	720	80	6041	38.1875	22.3125	22.6875	2152		X	A	9	SB 6320
	36	18-P95-19	29.86	855	95	6041	38.1875	22.3125	22.6875	2264		X	A	9	SB 6320

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are $\pm 1/16"$. Battery weights may vary $\pm 5\%$. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

THREE WHEEL SIT-DOWN RIDERS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity 6 Hr. Rate		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
SC4010-30, SC4510-30 38.8125 x 16.0625 x 22.8125	36	18-D85-13	17.81	510	85	6062	37.6875	15.4375	22.625	1507		X	A	9	SB6320
	36	18-H80-13	16.76	480	80	6062	37.6875	15.4375	22.625	1447		X	A	9	SB6320
	36	18-P95-13	19.90	570	95	6062	37.6875	15.4375	22.625	1522		X	A	9	SB6320
SC4020-30, SC4020-35 SC4520-30, SC4520-35 38.8125 x 20.5 x 22.8125	36	18-D85-17	23.75	680	85	6015	38.1875	20.0625	22.6875	2045		X	A	9	SB 6320
	36	18-H80-17	22.35	640	80	6015	38.1875	20.0625	22.6875	1963		X	A	9	SB 6320
	36	18-P95-17	26.54	760	95	6015	38.1875	20.0625	22.6875	2065		X	A	9	SB 6320
SC4040-30, SC4040-35 SC4540-35, SC4540-40 38.8125 x 24.875 x 22.8125	36	18-D85-21	29.68	850	85	6010	38.1875	24.5625	22.6875	2466		X	A	9	SB 6320
	36	18-H80-21	27.94	800	80	6010	38.1875	24.5625	22.6875	2367		X	A	9	SB 6320
	36	18-P95-21	33.17	950	95	6010	38.1875	24.5625	22.6875	2491		X	A	9	SB 6320

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

FOUR WHEEL SIT-DOWN RIDERS

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity 6 Hr. Rate		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
40FC, 50FC Standard Compartment 38.6875 x 27.1875 x 23	36	18-D85-23	32.65	935	85	6009	38.1875	26.9375	22.6875	2703		X	A	15	SB 6320
	36	18-H80-23	30.73	880	80	6009	38.1875	26.9375	22.6875	2595		X	A	15	SB 6320
	36	18-P95-23	36.49	1045	95	6009	38.1875	26.9375	22.6875	2730		X	A	15	SB 6320
	48	24-D85-17	31.66	680	85	7002	38.1875	26.6875	22.6875	2706		X	A	15	SB 6320
	48	24-H80-17	29.80	640	80	7002	38.1875	26.6875	22.6875	2598		X	A	15	SB 6320
	48	24-P95-17	35.39	760	95	7002	38.1875	26.6875	22.6875	2733		X	A	15	SB 6320
40FC, 50FC, 55FC, 60FC Optional Compartment #1 38.6875 x 32.875 x 23	36	18-D85-25	35.62	1020	85	6030	38.1875	29.1875	22.6875	2924		X	A	15	SB 6320
	36	18-H80-25	33.52	960	80	6030	38.1875	29.1875	22.6875	2807		X	A	15	SB 6320
	36	18-P95-25	39.81	1140	95	6030	38.1875	29.1875	22.6875	2953		X	A	15	SB 6320
	36	18-D85-27	38.59	1105	85	6026	38.1875	31.4375	22.6875	3144		X	A	15	SB 6320
	36	18-H80-27	36.32	1040	80	6026	38.1875	31.4375	22.6875	3018		X	A	15	SB 6320
	36	18-P95-27	43.13	1235	95	6026	38.1875	31.4375	22.6875	3175		X	A	15	SB 6320
	48	24-D85-19	35.62	765	85	7003	38.1875	29.6875	22.6875	2994		X	A	15	SB 6320
	48	24-H80-19	33.52	720	80	7003	38.1875	29.6875	22.6875	2874		X	A	15	SB 6320
	48	24-P95-19	39.81	855	95	7003	38.1875	29.6875	22.6875	3024		X	A	15	SB 6320
	48	24-D85-21	39.58	850	85	7004	38.1875	32.6875	22.6875	3279		X	A	15	SB 6320
	48	24-H80-21	37.25	800	80	7004	38.1875	32.6875	22.6875	3148		X	A	15	SB 6320
	48	24-P95-21	44.23	950	95	7004	38.1875	32.6875	22.6875	3312		X	A	15	SB 6320

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

FOUR WHEEL SIT-DOWN RIDERS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Length Pos. (in.)		
60FC, 50FC, 55FC Optional Compartment #2 38.6875 x 36.375 x 23	36	18-D85-29	41.55	1190	85	6021	38.1875	33.6875	22.6875	3394	X		A	15	SB 6320
	36	18-H80-29	39.11	1120	80	6021	38.1875	33.6875	22.6875	3258	X		A	15	SB 6320
	36	18-P95-29	46.44	1330	95	6021	38.1875	33.6875	22.6875	3428	X		A	15	SB 6320
	36	18-D85-31	44.52	1275	85	6164	38.1875	35.9375	22.6875	3619	X		A	15	SB 6320
	36	18-H80-31	41.90	1200	80	6164	38.1875	35.9375	22.6875	3474	X		A	15	SB 6320
	36	18-P95-31	49.76	1425	95	6164	38.1875	35.9375	22.6875	3655	X		A	15	SB 6320
	48	24-D85-23	43.53	935	85	7059	38.1875	35.6875	22.6875	3573	X		A	15	SB 6320
	48	24-H80-23	40.97	880	80	7059	38.1875	35.6875	22.6875	3430	X		A	15	SB 6320
	48	24-P95-23	48.66	1045	95	7059	38.1875	35.6875	22.6875	3609	X		A	15	SB 6320
FP40, FP50 38.6875 x 32.9375 x 22.75	36	18-D85-27	38.59	1105	85	6026	38.1875	31.4375	22.6875	3144	X		A	15	SB 6320
	36	18-H80-27	36.32	1040	80	6026	38.1875	31.4375	22.6875	3018	X		A	15	SB 6320
	36	18-P95-27	43.13	1235	95	6026	38.1875	31.4375	22.6875	3175	X		A	15	SB 6320
	48	24-D85-21	39.58	850	85	7004	38.1875	32.6875	22.6875	3279	X		A	15	SB 6320
	48	24-H80-21	37.25	800	80	7004	38.1875	32.6875	22.6875	3148	X		A	15	SB 6320
	48	24-P95-21	44.23	950	95	7004	38.1875	32.6875	22.6875	3312	X		A	15	SB 6320
FP60, FB40, FB50, FP55 Optional Compartment 38.6875 x 36.375 x 22.75	36	18-D85-31	44.52	1275	85	6164	38.1875	35.9375	22.6875	3619	X		A	15	SB 6320
	36	18-H80-31	41.90	1200	80	6164	38.1875	35.9375	22.6875	3474	X		A	15	SB 6320
	36	18-P95-31	49.76	1425	95	6164	38.1875	35.9375	22.6875	3655	X		A	15	SB 6320
	48	24-D85-23	43.53	935	85	7059	38.1875	35.6875	22.6875	3573	X		A	15	SB 6320
	48	24-H80-23	40.97	880	80	7059	38.1875	35.6875	22.6875	3430	X		A	15	SB 6320
	48	24-P95-23	48.66	1045	95	7059	38.1875	35.6875	22.6875	3609	X		A	15	SB 6320
FC4010-40, FC4010-50 FC4510-40, FC4510-50 FC4515-40, FC4515-50 38.6875 x 27.25 x 22.75	36	18-D85-23	32.65	935	85	6009	38.1875	26.9375	22.6875	2703	X		A	18	SB6320
	36	18-H80-23	30.73	880	80	6009	38.1875	26.9375	22.6875	2595	X		A	18	SB6320
	36	18-P95-23	36.49	1045	95	6009	38.1875	26.9375	22.6875	2730	X		A	18	SB6320
	48	24-D85-17	31.66	680	85	7002	38.1875	26.6875	22.6875	2706	X		A	18	SB6320
	48	24-H80-17	29.80	640	80	7002	38.1875	26.6875	22.6875	2598	X		A	18	SB6320
	48	24-P95-17	35.39	760	95	7002	38.1875	26.6875	22.6875	2733	X		A	18	SB6320
FC4020-40, FC4020-50 FC4020-55, FC4020-60 FC4520-40, FC4520-50 FC4520-55, FC4520-60 FC4525-40, FC4525-50 FC4525-55, FC4525-60 38.6875 x 32.9375 x 22.75	36	18-D85-27	38.59	1105	85	6026	38.1875	31.4375	22.6875	3144	X		A	18	SB6320
	36	18-H80-27	36.32	1040	80	6026	38.1875	31.4375	22.6875	3018	X		A	18	SB6320
	36	18-P95-27	43.13	1235	95	6026	38.1875	31.4375	22.6875	3175	X		A	18	SB6320
	48	24-D85-21	39.58	850	85	7004	38.1875	32.6875	22.6875	3279	X		A	18	SB6320
	48	24-H80-21	37.25	800	80	7004	38.1875	32.6875	22.6875	3148	X		A	18	SB6320
	48	24-P95-21	44.23	950	95	7004	38.1875	32.6875	22.6875	3312	X		A	18	SB6320

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

FOUR WHEEL SIT-DOWN RIDERS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
FC4040-50, FC4040-55	36	18-D85-31	44.52	1275	85	6164	38.1875	35.9375	22.6875	3619		X	A	18	SB6320
FC4040-60, FC4540-50	36	18-H80-31	41.90	1200	80	6164	38.1875	35.9375	22.6875	3474		X	A	18	SB6320
FC4540-55, FC4540-60	36	18-P95-31	49.76	1425	95	6164	38.1875	35.9375	22.6875	3655		X	A	18	SB6320
FC4545-50, FC4545-55	48	24-D85-23	43.53	935	85	7059	38.1875	35.6875	22.6875	3573		X	A	18	SB6320
FC4545-60	48	24-H80-23	40.97	880	80	7059	38.1875	35.6875	22.6875	3430		X	A	18	SB6320
38.6875 x 36.375 x 22.75	48	24-P95-23	48.66	1045	95	7059	38.1875	35.6875	22.6875	3609		X	A	18	SB6320

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

TURRET SIDE LOADER, TURRET STOCKPICKER

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
TSP	48	24-D125-17	46.56	1000	125	7024	38.1875	26.6875	30.5625	3761		X	A	9	SB 6320 W/996
38.75 x 27 x 31	48	24-H120-17	44.70	960	120	7024	38.1875	26.6875	30.5625	3723		X	A	9	SB 6320 W/996
	48	24-P140-17	52.15	1120	140	7024	38.1875	26.6875	30.5625	3799		X	A	9	SB 6320 W/996
TSP	48	24-D125-21	58.20	1250	125	7121	38.25	32.75	30.5625	4579		X	A	9	SB 6320 W/996
38.75 x 33 x 31	48	24-H120-21	55.87	1200	120	7121	38.25	32.75	30.5625	4533		X	A	9	SB 6320 W/996
	48	24-P140-21	65.18	1400	140	7121	38.25	32.75	30.5625	4625		X	A	9	SB 6320 W/996
TS, TSP	72	18-D125-11	21.83 ea	625	125	6016	37.8125	13.3125	30.5625	1852		X	A	9	SB 6320 W/996
38.5625 x 13.625 x 31	72	18-H120-11	20.95 ea	600	120	6016	37.8125	13.3125	30.5625	1833		X	A	9	SB 6320 W/996
See Note C	72	18-P140-11	24.44 ea	700	140	6016	37.8125	13.3125	30.5625	1871		X	A	9	SB 6320 W/996
TS, TSP	72	18-D125-13	26.19 ea	750	125	6005	37.8125	15.5625	30.5625	2166		X	A	9	SB 6320 W/996
38.5625 x 16.25 x 31	72	18-H120-13	25.14 ea	720	120	6005	37.8125	15.5625	30.5625	2144		X	A	9	SB 6320 W/996
See Note C	72	18-P140-13	29.33 ea	840	140	6005	37.8125	15.5625	30.5625	2188		X	A	9	SB 6320 W/996
TS, TSP	72	18-D125-15	30.56 ea	875	125	6045	38.1875	17.8125	30.5625	2486		X	A	9	SB 6320 W/996
38.6875 x 18 x 31	72	18-H120-15	29.33 ea	840	120	6045	38.1875	17.8125	30.5625	2461		X	A	9	SB 6320 W/996
See Note C	72	18-P140-15	34.22 ea	980	140	6045	38.1875	17.8125	30.5625	2511		X	A	9	SB 6320 W/996
TSP6000	48	24-D125-15	40.74	875	125	7403	44	23.5625	30.5625	3362		X	A	15	SB 6321
44.625 x 24.9375 x 31.25	48	24-H120-15	39.11	840	120	7403	44	23.5625	30.5625	3328		X	A	15	SB 6321
	48	24-P140-15	45.63	980	140	7403	44	23.5625	30.5625	3396		X	A	15	SB 6321

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

TURRET SIDE LOADER, TURRET STOCKPICKER (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	Length (in.)	
TSP6000 44.625 x 28.3125 x 31.25	48	24-D125-17	46.56	1000	125	7615	44	26.6875	30.5625	3854		X	A	15	SB 6321
	48	24-H120-17	44.70	960	120	7615	44	26.6875	30.5625	3815		X	A	15	SB 6321
	48	24-P140-17	52.15	1120	140	7615	44	26.6875	30.5625	3893		X	A	15	SB 6321
	48	24-D125-19	52.38	1125	125	7563	44.1875	25.5625	30.5625	4094		X	A	15	SB 6321
	48	24-H120-19	50.28	1080	120	7563	44.1875	25.5625	30.5625	4053		X	A	15	SB 6321
	48	24-P140-19	58.67	1260	140	7563	44.1875	25.5625	30.5625	4135		X	A	15	SB 6321
TSP6000 44.625 x 33.9375 x 31.25	48	24-D125-21	58.20	1250	125	7616	44	32.6875	30.5625	4697		X	A	15	SB 6321
	48	24-H120-21	55.87	1200	120	7616	44	32.6875	30.5625	4650		X	A	15	SB 6321
	48	24-P140-21	65.18	1400	140	7616	44	32.6875	30.5625	4744		X	A	15	SB 6321
	48	24-D125-23	64.02	1375	125	7613	44.5625	32.0625	30.625	5117		X	A	15	SB 6321
	48	24-H120-23	61.46	1320	120	7613	44.5625	32.0625	30.625	5066		X	A	15	SB 6321
	48	24-P140-23	71.70	1540	140	7613	44.5625	32.0625	30.625	5168		X	A	15	SB 6321

Note C: 72 volt TS and TSP models require two (2) 18 cell batteries

ea - KWH calculated for each 18-cell battery

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

Batteries listed are also available in the Max Power "P" Line which is a 10% increase of ampere hour capacity over the standard "D" Line. Refer to Table #2 of Selector Guide for "D" series to Max Power series cross reference table.

EAST PENN manufacturing co., inc.

Lyon Station, PA 19536-0147 • Phone: 610-682-6361 • Fax: 610-682-4212
www.dekabatteries.com • e-mail: epmmotve@eastpenn-deka.com

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.