



INDUSTRIAL BATTERIES

BT/PRIME MOVER

WALKIE, RIDER/WALKIE, TOW TRACTORS

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity 6 Hr. Rate KWH	A.H.	AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.	
							Length X	Width Y	Height Z		Yes	No	Pos.	(in.)		
RMX50 31.75 x 8.125 x Open	12	6-D100-11	cm	5.82	500	100	1167	31.25	7.75	26.1875	576	X		B	27	SB6329
	12	6-D85-11	cm	4.95	425	85	1061	31.25	7.75	23.1875	516	X		B	27	SB6329
	12	6-H80-11	cm	4.66	400	80	1061	31.25	7.75	23.1875	495	X		B	27	SB6329
	12	6-P95-11	cm	5.53	475	95	1061	31.25	7.75	23.1875	521	X		B	27	SB6329
	12	6-D100-13		6.98	600	100	1091	30.5	7.75	26.1875	613	X		B	15	SB6329
	12	6-D125-13		8.73	750	125	1092	30.5	7.75	31.0625	750	X		B	15	SB6329
	12	6-D85-13		5.94	510	85	1088	30.5	7.75	23.1875	538	X		B	15	SB6329
	12	6-H120-13		8.38	720	120	1092	30.5	7.75	31.0625	743	X		B	15	SB6329
	12	6-H80-13		5.59	480	80	1088	30.5	7.75	23.1875	516	X		B	15	SB6329
	12	6-P140-13		9.78	840	140	1092	30.5	7.75	31.0625	758	X		B	15	SB6329
	12	6-P95-13		6.63	570	95	1088	30.5	7.75	23.1875	543	X		B	15	SB6329
	RMX65, RMX80 31.75 x 8.125 x Open Optional Compartment	24	(4) 8GGC2	pm	3.60	155		3801	25.5	7.5	24.5	340	X		B	26
24		12-D100-5		4.66	200	100	3611	27.1875	6.4375	26.25	496	X		B	15	SB6329
24		12-D100-5	cm	4.66	200	100	3757	29.375	6.4375	26.1875	513	X		B	24	SB6329
24		12-D85-5		3.96	170	85	3081	24.625	6.4375	23.1875	418	X		B	15	SB6329
24		12-H80-5		3.72	160	80	3081	24.625	6.4375	23.1875	401	X		B	15	SB6329
24		12-P95-5		4.42	190	95	3081	24.625	6.4375	23.1875	422	X		B	15	SB6329
RMX50 Optional Compartment 31.75 x 13.3125 x Open	12	6-D100-25		13.97	1200	100	1137	28.9375	12.875	26.25	1153	X		B	15	SB6329
	12	6-D125-27		18.92	1625	125	1241	31.1875	12.875	31.125	1504	X		B	15	SB6329
	12	6-D85-27		12.86	1105	85	1112	31.1875	12.875	23.25	1072	X		B	15	SB6329
	12	6-H80-27		12.11	1040	80	1112	31.1875	12.875	23.25	1029	X		B	15	SB6329
	12	6-P140-27		21.18	1820	140	1241	31.1875	12.875	31.125	1519	X		B	15	SB6329
	12	6-P95-27		14.38	1235	95	1112	31.1875	12.875	23.25	1083	X		B	15	SB6329

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE, RIDER/WALKIE, TOW TRACTORS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads		Standard Conn.	
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Length Pos. (in.)			
PX40, PX40R 31.375 x 8 x Open	12	6-D160-9	7.45	640	160	1012	26.4375	7.25	31.0625	673	X		B	15	SB6325	
	12	6-D100-13	6.98	600	100	1091	30.5	7.75	26.1875	613	X		B	15	SB6325	
	12	6-D125-13	8.73	750	125	1092	30.5	7.75	31.0625	750	X		B	15	SB6325	
	12	6-D85-13	5.94	510	85	1088	30.5	7.75	23.1875	538	X		B	15	SB6325	
	12	6-H120-13	8.38	720	120	1092	30.5	7.75	31.0625	743	X		B	15	SB6325	
	12	6-H80-13	5.59	480	80	1088	30.5	7.75	23.1875	516	X		B	15	SB6325	
	12	6-P140-13	9.78	840	140	1092	30.5	7.75	31.0625	758	X		B	15	SB6325	
	12	6-P95-13	6.63	570	95	1088	30.5	7.75	23.1875	543	X		B	15	SB6325	
PMX 28.25 x 9 x 24	12	6-D85-9	cm	3.96	340	85	1157	26.75	7.75	23.1875	436	X		B	27	SB6328
	12	6-H80-9	cm	3.72	320	80	1157	26.75	7.75	23.1875	419	X		B	27	SB6328
	12	6-P95-9	cm	4.42	380	95	1157	26.75	7.75	23.1875	440	X		B	27	SB6328
	12	6-D85-11		4.95	425	85	1087	25.875	7.75	23.1875	455	X		B	15	SB6328
	12	6-H80-11		4.66	400	80	1087	25.875	7.75	23.1875	437	X		B	15	SB6328
	12	6-P95-11		5.53	475	95	1087	25.875	7.75	23.1875	460	X		B	15	SB6328
PMX, PMX45, PPT45 28.25 x 9 x 24	24	12-D85-5	cm	3.96	170	85	3167	24.25	8.3125	23.1875	464	X		B	24	SB6329
	24	12-H80-5	cm	3.72	160	80	3167	24.25	8.3125	23.1875	445	X		B	24	SB6329
	24	12-P95-5	cm	4.42	190	95	3167	24.25	8.3125	23.1875	469	X		B	24	SB6329
	24	12-D85-7		5.94	255	85	3042	25.25	8.5625	23.1875	567	X		B	15	SB6329
	24	12-H80-7		5.59	240	80	3042	25.25	8.5625	23.1875	544	X		B	15	SB6329
	24	12-P95-7		6.63	285	95	3042	25.25	8.5625	23.1875	573	X		B	15	SB6329
PMX Optional Compartment 31.25 x 9 x 24	12	6-D85-13		5.94	510	85	1088	30.5	7.75	23.1875	538	X		B	15	SB6328
	12	6-H80-13		5.59	480	80	1088	30.5	7.75	23.1875	516	X		B	15	SB6328
	12	6-P95-13		6.63	570	95	1088	30.5	7.75	23.1875	543	X		B	15	SB6328
PMX, PPT45, QMX Optional Compartment 31.25 x 9 x 24	24	12-D85-7		5.94	255	85	3447	30.5	8.5625	23.25	595	X		B	15	SB6329
	24	12-D85-7	cm	5.94	255	85	3415	30.5	8.5625	23.1875	606	X		B	24	SB6329
	24	12-D85-7		5.94	255	85	3042	25.25	8.5625	23.1875	567	X		B	15	SB6329
	24	12-H80-7		5.59	240	80	3447	30.5	8.5625	23.25	571	X		B	15	SB6329
	24	12-H80-7	cm	5.59	240	80	3415	30.5	8.5625	23.1875	582	X		B	24	SB6329
	24	12-H80-7		5.59	240	80	3042	25.25	8.5625	23.1875	544	X		B	15	SB6329
	24	12-P95-7		6.63	285	95	3447	30.5	8.5625	23.25	601	X		B	15	SB6329
	24	12-P95-7	cm	6.63	285	95	3415	30.5	8.5625	23.1875	612	X		B	24	SB6329
	24	12-P95-7		6.63	285	95	3042	25.25	8.5625	23.1875	573	X		B	15	SB6329

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE, RIDER/WALKIE, TOW TRACTORS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type		Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads		Standard Conn.
				6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Length Pos. (in.)		
PMX1, PMX2 29 x 8.75 x 26.5	12	6-D85-9	cm	3.96	340	85	1157	26.75	7.75	23.1875	436	X		B	27	SB6325
	12	6-H80-9	cm	3.72	320	80	1157	26.75	7.75	23.1875	419	X		B	27	SB6325
	12	6-P95-9	cm	4.42	380	95	1157	26.75	7.75	23.1875	440	X		B	27	SB6325
	12	6-D100-11		5.82	500	100	1089	25.875	7.75	26.1875	522	X		B	15	SB6325
	12	6-D85-11		4.95	425	85	1087	25.875	7.75	23.1875	455	X		B	15	SB6325
	12	6-H80-11		4.66	400	80	1087	25.875	7.75	23.1875	437	X		B	15	SB6325
	12	6-P95-11		5.53	475	95	1087	25.875	7.75	23.1875	460	X		B	15	SB6325
PMX1, PMX2 29 x 8.75 x 26.5	24	12-D85-5	cm	3.96	170	85	3167	24.25	8.3125	23.1875	464	X		B	24	SB6325
	24	12-H80-5	cm	3.72	160	80	3167	24.25	8.3125	23.1875	445	X		B	24	SB6325
	24	12-P95-5	cm	4.42	190	95	3167	24.25	8.3125	23.1875	469	X		B	24	SB6325
	24	12-D100-7		6.98	300	100	3123	25.3125	8.5625	26.1875	649	X		B	15	SB6325
	24	12-D85-7		5.94	255	85	3042	25.25	8.5625	23.1875	567	X		B	15	SB6325
	24	12-H80-7		5.59	240	80	3042	25.25	8.5625	23.1875	544	X		B	15	SB6325
	24	12-P95-7		6.63	285	95	3042	25.25	8.5625	23.1875	573	X		B	15	SB6325
MX50, MX65, PE45, PE4SR PE60, PE60R, PE60W, PE80 RX50, RX65, SN20, SN30 TES0, TT50 32 x 8 x Open	12	6-D100-11	cm	5.82	500	100	1167	31.25	7.75	26.1875	576	X		B	27	SB6325
	12	6-D85-11	cm	4.95	425	85	1061	31.25	7.75	23.1875	516	X		B	27	SB6325
	12	6-H80-11	cm	4.66	400	80	1061	31.25	7.75	23.1875	495	X		B	27	SB6325
	12	6-P95-11	cm	5.53	475	95	1061	31.25	7.75	23.1875	521	X		B	27	SB6325
	12	6-D100-13		6.98	600	100	1091	30.5	7.75	26.1875	613	X		B	15	SB6325
	12	6-D125-13		8.73	750	125	1092	30.5	7.75	31.0625	750	X		B	15	SB6325
	12	6-D85-13		5.94	510	85	1088	30.5	7.75	23.1875	538	X		B	15	SB6325
	12	6-H120-13		8.38	720	120	1092	30.5	7.75	31.0625	743	X		B	15	SB6325
	12	6-H80-13		5.59	480	80	1088	30.5	7.75	23.1875	516	X		B	15	SB6325
	12	6-P140-13		9.78	840	140	1092	30.5	7.75	31.0625	758	X		B	15	SB6325
	12	6-P95-13		6.63	570	95	1088	30.5	7.75	23.1875	543	X		B	15	SB6325
HT45, HT60, HT60W HT80W, HX65, HX80, MX50 MX65, PE45, PE45R, PE60 PE60R, PE60W, PE80 RMX50, RX50, RX65, SN20 SN30, SN40, SR30, TE70 TT70 32 x 13.5 x Open	24	12-D100-11	cm	11.64	500	100	3539	31.375	12.875	26.25	1068	X		B	30	SB6325
	24	12-D85-11	cm	9.89	425	85	3163	31.375	12.875	23.25	965	X		B	30	SB6325
	24	12-H80-11	cm	9.31	400	80	3163	31.375	12.875	23.25	926	X		B	30	SB6325
	24	12-P95-11	cm	11.06	475	95	3163	31.375	12.875	23.25	975	X		B	30	SB6325
	24	12-D100-13		13.97	600	100	3015	30.5625	12.75	26.25	1188	X		B	15	SB6325
	24	12-D125-13		17.46	750	125	3008	30.5625	12.75	31.125	1455	X		B	15	SB6325
	24	12-D85-13		11.87	510	85	3019	30.5625	12.75	23.25	1049	X		B	15	SB6325
	24	12-H120-13		16.76	720	120	3008	30.5625	12.75	31.125	1440	X		B	15	SB6325
	24	12-H80-13		11.17	480	80	3019	30.5625	12.75	23.25	1007	X		B	15	SB6325
	24	12-P140-13		19.56	840	140	3008	30.5625	12.75	31.125	1470	X		B	15	SB6325
24	12-P95-13		13.27	570	95	3019	30.5625	12.75	23.25	1059	X		B	15	SB6325	

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE, RIDER/WALKIE, TOW TRACTORS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity 6 Hr. Rate		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.	
			KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)		
SC20, SC25, SC30 31.1875 x 13.75 x 24.625	12	6-D85-25	11.87	1020	85	1228	28.9375	12.875	23.25	1002	X		B	15	SB6328	
	12	6-H80-25	11.17	960	80	1228	28.9375	12.875	23.25	962	X		B	15	SB6328	
	12	6-P95-25	13.27	1140	95	1228	28.9375	12.875	23.25	1012	X		B	15	SB6328	
SC20, SC25, SC30, SC40 31.1875 x 13.75 x 24.625	24	12-D85-11	9.89	425	85	3414	30.6875	13.1875	23.25	960	X		B	15	SB6329	
	24	12-H80-11	9.31	400	80	3414	30.6875	13.1875	23.25	922	X		B	15	SB6329	
	24	12-P95-11	11.06	475	95	3414	30.6875	13.1875	23.25	970	X		B	15	SB6329	
	24	12-D85-13	11.87	510	85	3019	30.5625	12.75	23.25	1049	X		B	15	SB6329	
	24	12-H80-13	11.17	480	80	3019	30.5625	12.75	23.25	1007	X		B	15	SB6329	
	24	12-P95-13	13.27	570	95	3019	30.5625	12.75	23.25	1059	X		B	15	SB6329	
CSX20, CSX30, CSX40 WRX30, WSX30, WSX40 32.3125 x 13.3125 x Open	24	12-D100-11	cm	11.64	500	100	3539	31.375	12.875	26.25	1068	X		B	30	SB6329
	24	12-D100-13		13.97	600	100	3015	30.5625	12.75	26.25	1188	X		B	20	SB6329
	24	12-D125-13		17.46	750	125	3008	30.5625	12.75	31.125	1455	X		B	20	SB6329
	24	12-D85-13		11.87	510	85	3019	30.5625	12.75	23.25	1049	X		B	20	SB6329
	24	12-H120-13		16.76	720	120	3008	30.5625	12.75	31.125	1440	X		B	20	SB6329
	24	12-H80-13		11.17	480	80	3019	30.5625	12.75	23.25	1007	X		B	20	SB6329
	24	12-P140-13		19.56	840	140	3008	30.5625	12.75	31.125	1470	X		B	20	SB6329
	24	12-P95-13		13.27	570	95	3019	30.5625	12.75	23.25	1059	X		B	20	SB6329
CMX60, CMX80, HMX50 HMX65, HMX80, RMX65 RMX80, TMX 31.75 x 13.3125 x Open	24	12-D100-11	cm	11.64	500	100	3539	31.375	12.875	26.25	1068	X		B	30	SB6329
	24	12-D100-13		13.97	600	100	3015	30.5625	12.75	26.25	1188	X		B	15	SB6329
	24	12-D125-13		17.46	750	125	3008	30.5625	12.75	31.125	1455	X		B	15	SB6329
	24	12-D85-13		11.87	510	85	3019	30.5625	12.75	23.25	1049	X		B	15	SB6329
	24	12-H120-13		16.76	720	120	3008	30.5625	12.75	31.125	1440	X		B	15	SB6329
	24	12-H80-13		11.17	480	80	3019	30.5625	12.75	23.25	1007	X		B	15	SB6329
	24	12-P140-13		19.56	840	140	3008	30.5625	12.75	31.125	1470	X		B	15	SB6329
	24	12-P95-13		13.27	570	95	3019	30.5625	12.75	23.25	1059	X		B	15	SB6329
CSX10, WSX22 32.3125 x 9 x Open	24	12-D100-7		6.98	300	100	3346	30.5	8.5625	26.1875	686	X		B	20	SB6329
	24	12-D100-7		6.98	300	100	3123	25.3125	8.5625	26.1875	649	X		B	20	SB6329
	24	12-D85-7	cm	5.94	255	85	3415	30.5	8.5625	23.1875	606	X		B	24	SB6329
	24	12-D85-7		5.94	255	85	3042	25.25	8.5625	23.1875	567	X		B	20	SB6329
	24	12-H80-7	cm	5.59	240	80	3415	30.5	8.5625	23.1875	582	X		B	24	SB6329
	24	12-H80-7		5.59	240	80	3042	25.25	8.5625	23.1875	544	X		B	20	SB6329
	24	12-P95-7	cm	6.63	285	95	3415	30.5	8.5625	23.1875	612	X		B	24	SB6329
	24	12-P95-7		6.63	285	95	3042	25.25	8.5625	23.1875	573	X		B	20	SB6329

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE, RIDER/WALKIE, TOW TRACTORS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
WSX20, WSX25 27.375 x 9 x Open	24	(4) 8GGC2 pm	3.60	155		3800	25.5	8.5625	24.5	340	X		B	26	SB6329
	24	12-D100-5 cm	4.66	200	100	3526	24.25	8.3125	26.1875	514	X		B	24	SB6329
	24	12-D100-7	6.98	300	100	3123	25.3125	8.5625	26.1875	649	X		B	15	SB6329
	24	12-D85-7	5.94	255	85	3042	25.25	8.5625	23.1875	567	X		B	15	SB6329
	24	12-H80-7	5.59	240	80	3042	25.25	8.5625	23.1875	544	X		B	15	SB6329
	24	12-P95-7	6.63	285	95	3042	25.25	8.5625	23.1875	573	X		B	15	SB6329

cm - Charge-Mate includes on board charger.
 pm - Powr-Mate includes on board charger.
 H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

ORDER SELECTORS

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
OE15C 32 x 8 x 26.5	12	6-D100-13	6.98	600	100	1047	30.875	7.75	25.5625	566		X	B	15	SB6325
	12	6-D85-13	5.94	510	85	1069	30.5625	7.75	22.5625	578		X	B	15	SB6325
	12	6-H80-13	5.59	480	80	1069	30.5625	7.75	22.5625	555		X	B	15	SB6325
	12	6-P95-13	6.63	570	95	1069	30.5625	7.75	22.5625	584		X	B	15	SB6325
OE15C 32 x 8 x 26.5 Min. Battery Wt. - 500 lbs.	24	12-D85-5	3.96	170	85	3383	24.75	7.5	22.5625	426		X	B	15	SB6325
	24	12-H80-5	3.72	160	80	3383	24.75	7.5	22.5625	409		X	B	15	SB6325
	24	12-P95-5	4.42	190	95	3383	24.75	7.5	22.5625	430		X	B	15	SB6325
OE15C 32 x 13.5 x 26.5	12	6-D85-25	11.87	1020	85	1031	28.9375	12.875	22.625	983		X	B	15	SB6325
	12	6-H80-25	11.17	960	80	1031	28.9375	12.875	22.625	944		X	B	15	SB6325
	12	6-P95-25	13.27	1140	95	1031	28.9375	12.875	22.625	993		X	B	15	SB6325
OE15C 32 x 13.5 x 26.5	24	12-D100-13	13.97	600	100	3104	30.5625	12.75	25.625	1165		X	B	15	SB6329
	24	12-D85-13	11.87	510	85	3082	30.5625	12.75	22.625	1025		X	B	15	SB6329
	24	12-H80-13	11.17	480	80	3082	30.5625	12.75	22.625	984		X	B	15	SB6329
	24	12-P95-13	13.27	570	95	3082	30.5625	12.75	22.625	1035		X	B	15	SB6329
OE30, OE30B, OE30C, OE35 36.25 x 13.875 x 31.5625	24	12-D160-11	18.62	800	160	3025	35.0625	13.1875	30.5	1647		X	B	18	SB6322
	24	12-D125-15	20.37	875	125	3036	35.0625	12.875	30.5	1651		X	B	18	SB6322
	24	12-H120-15	19.56	840	120	3036	35.0625	12.875	30.5	1634		X	B	18	SB6322
	24	12-P140-15	22.81	980	140	3036	35.0625	12.875	30.5	1668		X	B	18	SB6322

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

ORDER SELECTORS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	Length (in.)	
OE30C, OE35 38.25 x 13.875 x 31.5625	36	18-D125-11	21.83	625	125	6016	37.8125	13.3125	30.5625	1852		X	B	18	SB6320
	36	18-H120-11	20.95	600	120	6016	37.8125	13.3125	30.5625	1833		X	B	18	SB6320
	36	18-P140-11	24.44	700	140	6016	37.8125	13.3125	30.5625	1871		X	B	18	SB6320

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

STAND-UP RIDERS, REACH

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	Length (in.)	
RC20, RC25, RC30, RC40 36.25 x 12 x 33.5	24	12-D160-9	14.90	640	160	3007	35.062	10.937	31.125	1417	X		B	15	SB6325
	24	12-D125-13	17.46	750	125	3179	35.5625	11.5625	31.125	1475	X		B	15	SB6325
	24	12-H120-13	16.76	720	120	3179	35.5625	11.5625	31.125	1460	X		B	15	SB6325
	24	12-P140-13	19.56	840	140	3179	35.5625	11.5625	31.125	1490	X		B	15	SB6325
RR20, RR30, RS20, RS30 RS40 36.25 x 12 x 33.5	24	12-D160-9	14.90	640	160	3511	35.0625	10.9375	30.5	1309		X	B	15	SB6325
	24	12-D125-13	17.46	750	125	3176	35.5625	11.5625	30.5	1457		X	B	15	SB6325
	24	12-H120-13	16.76	720	120	3176	35.5625	11.5625	30.5	1442		X	B	15	SB6325
	24	12-P140-13	19.56	840	140	3176	35.5625	11.5625	30.5	1472		X	B	15	SB6325
RC30, RC40 36.25 x 16.5 x 33.5	24	12-D160-13	22.35	960	160	3002	35.25	15.562	31.1875	1965	X		B	15	SB6325
	24	12-D125-15	20.37	875	125	3039	35.0625	12.875	31.125	1674	X		B	15	SB6325
	24	12-H120-15	19.56	840	120	3039	35.0625	12.875	31.125	1657	X		B	15	SB6325
	24	12-P140-15	22.81	980	140	3039	35.0625	12.875	31.125	1691	X		B	15	SB6325
RR20, RR30, RR30C, RR34 RR34B, RS20, RS30, RS40 36.25 x 16.5 x 33.5	24	12-D160-13	22.35	960	160	3049	35.25	15.5625	30.5625	1985		X	B	15	SB6325
	24	12-D125-15	20.37	875	125	3036	35.0625	12.875	30.5	1651		X	B	15	SB6325
	24	12-H120-15	19.56	840	120	3036	35.0625	12.875	30.5	1634		X	B	15	SB6325
	24	12-P140-15	22.81	980	140	3036	35.0625	12.875	30.5	1668		X	B	15	SB6325
RR30, RR30B, RR30C, RR34 RR34B, RR40, RR40B, RR45 RR45B, RR45DR, RR45DRZ RR45Z, RS40, RS40B RS40C, RS50, RS50B 38.75 x 14.5 x 32	24	12-D160-11	18.62	800	160	3025	35.0625	13.1875	30.5	1647		X	B	21	SB6320
	24	12-D125-15	20.37	875	125	3036	35.0625	12.875	30.5	1651		X	B	21	SB6320
	24	12-H120-15	19.56	840	120	3036	35.0625	12.875	30.5	1634		X	B	21	SB6320
	24	12-P140-15	22.81	980	140	3036	35.0625	12.875	30.5	1668		X	B	21	SB6320
	24	12-D125-17	23.28	1000	125	3127	38.1875	13.5	30.5625	1944		X	B	21	SB6320
	24	12-H120-17	22.35	960	120	3127	38.1875	13.5	30.5625	1925		X	B	21	SB6320
24	12-P140-17	26.07	1120	140	3127	38.1875	13.5	30.5625	1963		X	B	21	SB6320	

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

STAND-UP RIDERS, REACH (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity 6 Hr. Rate		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
RR30, RR30B, RR30C, RR34	36	18-D125-11	21.83	625	125	6016	37.8125	13.3125	30.5625	1852		X	B	21	SB6320
RR34B, RR40, RR40B, RR45	36	18-H120-11	20.95	600	120	6016	37.8125	13.3125	30.5625	1833		X	B	21	SB6320
RR45B, RR45DR, RR45DRZ	36	18-P140-11	24.44	700	140	6016	37.8125	13.3125	30.5625	1871		X	B	21	SB6320
RR45Z, RS40, RS40B															
RS40C, RS50, RS50B															
38.75 x 14.5 x 32															
RR30B, RR34B, RR40	24	12-D160-13	22.35	960	160	3049	35.25	15.5625	30.5625	1985		X	B	21	SB6320
RR40B, RR45, RR45B	24	12-D125-17	23.28	1000	125	3127	38.1875	13.5	30.5625	1944		X	B	21	SB6320
RR45DR, RR45DRZ, RR45Z	24	12-H120-17	22.35	960	120	3127	38.1875	13.5	30.5625	1925		X	B	21	SB6320
RS40, RS40B, RS40C, RS50	24	12-P140-17	26.07	1120	140	3127	38.1875	13.5	30.5625	1963		X	B	21	SB6320
RS50B	24	12-D125-19	26.19	1125	125	3134	38.1875	15	30.5625	2126		X	B	21	SB6320
38.75 x 16.5 x 32	24	12-H120-19	25.14	1080	120	3134	38.1875	15	30.5625	2105		X	B	21	SB6320
	24	12-P140-19	29.33	1260	140	3134	38.1875	15	30.5625	2147		X	B	21	SB6320
RC30B, RR30, RR30C, RR34	36	18-D125-13	26.19	750	125	6005	37.8125	15.5625	30.5625	2166		X	B	21	SB6320
RR40, RR45, RR45DR	36	18-H120-13	25.14	720	120	6005	37.8125	15.5625	30.5625	2144		X	B	21	SB6320
RR45DRZ, RR45Z, RS40	36	18-P140-13	29.33	840	140	6005	37.8125	15.5625	30.5625	2188		X	B	21	SB6320
RS40C, RS50															
38.75 x 16.5 x 32															
RR30B, RR34B, RR40B	36	18-D125-13	26.19	750	125	6005	37.8125	15.5625	30.5625	2166		X	B	21	SB6320
RR45B, RR45DR, RR45DRZ	36	18-H120-13	25.14	720	120	6005	37.8125	15.5625	30.5625	2144		X	B	21	SB6320
RR45Z, RS40B, RS50B	36	18-P140-13	29.33	840	140	6005	37.8125	15.5625	30.5625	2188		X	B	21	SB6320
38.75 x 16.5 x 32															
RR45, RR45DR, RR45DRZ	24	12-D125-25	34.92	1500	125	3545	38.1875	19.5	30.5	2453		X	B	21	SB6322
RR45Z	24	12-H120-25	33.52	1440	120	3545	38.1875	19.5	30.5	2428		X	B	21	SB6322
38.75 x 21 x 32	24	12-P140-25	39.11	1680	140	3545	38.1875	19.5	30.5	2478		X	B	21	SB6322
RR45DR, RR45DRZ, RR45Z	36	18-D125-17	34.92	1000	125	6069	38.1875	20.0625	30.5625	2836		X	B	21	SB6320
RS50B	36	18-H120-17	33.52	960	120	6069	38.1875	20.0625	30.5625	2808		X	B	21	SB6320
38.75 x 21 x 32	36	18-P140-17	39.11	1120	140	6069	38.1875	20.0625	30.5625	2864		X	B	21	SB6320
RRX35, RSX40, RSX50	24	12-D160-13	22.35	960	160	3780	37.875	15.5625	30.5625	2113		X	C	15	SB6322
RTX35	24	12-D125-19	26.19	1125	125	3134	38.1875	15	30.5625	2126		X	C	15	SB6322
38.75 x 16.375 x 32	24	12-H120-19	25.14	1080	120	3134	38.1875	15	30.5625	2105		X	C	15	SB6322
Min. Battery Wt. - 2000 lbs.	24	12-P140-19	29.33	1260	140	3134	38.1875	15	30.5625	2147		X	C	15	SB6322

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

STAND-UP RIDERS, REACH (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity 6 Hr. Rate		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
RDX30, RRX35, RRX45	36	18-D125-13	26.19	750	125	6005	37.8125	15.5625	30.5625	2166		X	C	15	SB6320
RSX40, RSX50, RTX30DR	36	18-H120-13	25.14	720	120	6005	37.8125	15.5625	30.5625	2144		X	C	15	SB6320
RTX35, RTX45	36	18-P140-13	29.33	840	140	6005	37.8125	15.5625	30.5625	2188		X	C	15	SB6320
38.75 x 16.375 x 32															
RDX30, RRX45, RTX45	36	18-D125-17	34.92	1000	125	6069	38.1875	20.0625	30.5625	2836		X	C	15	SB6320
38.75 x 20.875 x 32	36	18-H120-17	33.52	960	120	6069	38.1875	20.0625	30.5625	2808		X	C	15	SB6320
	36	18-P140-17	39.11	1120	140	6069	38.1875	20.0625	30.5625	2864		X	C	15	SB6320
RCX30	36	18-D125-13	26.19	750	125	6005	37.8125	15.5625	30.5625	2166		X	C	25	SB6320
38.875 x 16.0625 x 31.5	36	18-H120-13	25.14	720	120	6005	37.8125	15.5625	30.5625	2144		X	C	25	SB6320
	36	18-P140-13	29.33	840	140	6005	37.8125	15.5625	30.5625	2188		X	C	25	SB6320
RCX35	36	18-D125-15	30.56	875	125	6045	38.1875	17.8125	30.5625	2486		X	C	25	SB6320
38.875 x 18.3125 x 31.5	36	18-H120-15	29.33	840	120	6045	38.1875	17.8125	30.5625	2461		X	C	25	SB6320
	36	18-P140-15	34.22	980	140	6045	38.1875	17.8125	30.5625	2511		X	C	25	SB6320
RCX40, RCX45, RCX50	36	18-D125-17	34.92	1000	125	6069	38.1875	20.0625	30.5625	2836		X	C	25	SB6320
38.875 x 20.75 x 31.5	36	18-H120-17	33.52	960	120	6069	38.1875	20.0625	30.5625	2808		X	C	25	SB6320
	36	18-P140-17	39.11	1120	140	6069	38.1875	20.0625	30.5625	2864		X	C	25	SB6320
RRX35, RSX40, RTX35	24	12-D125-15	20.37	875	125	3036	35.0625	12.875	30.5	1651		X	C	15	SB6322
38.75 x 14.375 x 32	24	12-H120-15	19.56	840	120	3036	35.0625	12.875	30.5	1634		X	C	15	SB6322
	24	12-P140-15	22.81	980	140	3036	35.0625	12.875	30.5	1668		X	C	15	SB6322
	24	12-D125-17	23.28	1000	125	3127	38.1875	13.5	30.5625	1944		X	C	15	SB6322
	24	12-H120-17	22.35	960	120	3127	38.1875	13.5	30.5625	1925		X	C	15	SB6322
	24	12-P140-17	26.07	1120	140	3127	38.1875	13.5	30.5625	1963		X	C	15	SB6322
RRX35, RSX40, RTX35	36	18-D125-11	21.83	625	125	6016	37.8125	13.3125	30.5625	1852		X	C	15	SB6320
38.75 x 14.375 x 32	36	18-H120-11	20.95	600	120	6016	37.8125	13.3125	30.5625	1833		X	C	15	SB6320
	36	18-P140-11	24.44	700	140	6016	37.8125	13.3125	30.5625	1871		X	C	15	SB6320
RTX35	24	12-D160-13	22.35	960	160	3780	37.875	15.5625	30.5625	2113		X	C	15	SB6322
38.75 x 16.375 x 32	24	12-D125-19	26.19	1125	125	3134	38.1875	15	30.5625	2126		X	C	15	SB6322
Optional Compartment	24	12-H120-19	25.14	1080	120	3134	38.1875	15	30.5625	2105		X	C	15	SB6322
Min. Battery Wt. - 2000 lbs.	24	12-P140-19	29.33	1260	140	3134	38.1875	15	30.5625	2147		X	C	15	SB6322

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

STAND-UP RIDERS, REACH (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity 6 Hr. Rate		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
RTX35	36	18-D125-13	26.19	750	125	6005	37.8125	15.5625	30.5625	2166		X	C	15	SB6320
38.75 x 16.375 x 32	36	18-H120-13	25.14	720	120	6005	37.8125	15.5625	30.5625	2144		X	C	15	SB6320
Optional Compartment	36	18-P140-13	29.33	840	140	6005	37.8125	15.5625	30.5625	2188		X	C	15	SB6320
RTX	36	18-D125-17	34.92	1000	125	6069	38.1875	20.0625	30.5625	2836		X	C	15	SB6320
38.75 x 20.875 x 32	36	18-H120-17	33.52	960	120	6069	38.1875	20.0625	30.5625	2808		X	C	15	SB6320
Optional Compartment	36	18-P140-17	39.11	1120	140	6069	38.1875	20.0625	30.5625	2864		X	C	15	SB6320

sp - Special tray IST3780 includes steel plates added for minimum weight requirement.
H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

NARROW AISLE REACH/TURRET TRUCK

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity 6 Hr. Rate		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
RT30, RT35, RT45	48	24-D125-7	17.46	375	125	7227	40.9375	13.375	34.5	1683		X	Mounted*	SB6321	
"Compact"	48	24-H120-7	16.76	360	120	7227	40.9375	13.375	34.5	1666		X	Mounted*	SB6321	
41.5 x 13.5 x 34.5	48	24-P140-7	19.56	420	140	7227	40.9375	13.375	34.5	1700		X	Mounted*	SB6321	
RT30, RT35, RT45	48	24-D125-9	23.28	500	125	7301	40.9375	16.9375	34.5	2088		X	Mounted*	SB6321	
"Compact"	48	24-H120-9	22.35	480	120	7301	40.9375	16.9375	34.5	2067		X	Mounted*	SB6321	
41.5 x 17 x 34.5	48	24-P140-9	26.07	560	140	7301	40.9375	16.9375	34.5	2109		X	Mounted*	SB6321	
RRN2	48	24-D125-7	17.46	375	125	7358	40.9375	13.375	36.4375	1701		X	Mounted*	SB6321	
41.5 x 13.5 x 36.4375	48	24-D125-7	17.46	375	125	7348	40.9375	13.375	35.625	1677		X	Mounted*	SB6321	
	48	24-H120-7	16.76	360	120	7358	40.9375	13.375	36.4375	1684		X	Mounted*	SB6321	
	48	24-H120-7	16.76	360	120	7348	40.9375	13.375	35.625	1660		X	Mounted*	SB6321	
	48	24-P140-7	19.56	420	140	7358	40.9375	13.375	36.4375	1718		X	Mounted*	SB6321	
	48	24-P140-7	19.56	420	140	7348	40.9375	13.375	35.625	1694		X	Mounted*	SB6321	
RRN3												X	Mounted*	SB6321	
41.5 x 17 x 36.4375															

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are $\pm 1/16"$. Battery weights may vary $\pm 5\%$. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

NARROW AISLE REACH/TURRET TRUCK (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length Pos. (in.)	Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No		
RRB2, RRB3, RRB5, RRB6 RRB7, RRB8, RRE2, RRE3 RRE5, RRE6, RRE7, RRE8 RT30, RT35, RT40, RT45 RT50, TRT22, TRT28 TRT33 47.75 x 11 x 33											X		Mounted*	SB6321
RRB2, RRB3, RRB5, RRB6 RRB7, RRB8, RRE2, RRE3 RRE5, RRE6, RRE7, RRE8 RT30, RT30C, RT35, RT35C RT40, RT40C, RT44, RT44C RT45, RT50, TRT22, TRT28 TRT33 47.75 x 13.5 x 33											X		Mounted*	SB6321
RRB2, RRB3, RRB5, RRB6 RRB7, RRB8, RRE2, RRE3 RRE5, RRE6, RRE7, RRE8 RT30, RT30C, RT35, RT35C RT40, RT44, RT44C, RT45 RT50, TRT22, TRT28 TRT33 47.75 x 16.5 x 33											X		Mounted*	SB6321
RRB2, RRB3, RRB5, RRB6 RRB7, RRB8, RRE2, RRE3 RRE5, RRE6, RRE7, RRE8 RT30, RT35, RT40, RT45 RT50, TRT22, TRT28 TRT33 47.75 x 19.5625 x 33											X		Mounted*	SB6321

- * Consult Factory
- * Conforms to European Standards with Retaining Hook and Special Machined Tray Bottom Accessories.
- sp - Special tray IST7227 includes retaining hook and machined bottom rails for RT30.
- sp - Special tray IST7301 includes retaining hook and machined bottom rails for RT30.
- sp - Special tray IST7348 includes retaining hook and bottom plates for RRB2 with side roll out.
- sp - Special tray IST7358 includes retaining hook and machined bottom rails for RRB2 with keys.
- H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

Batteries listed are also available in the Max Power "P" Line which is a 10% increase of ampere hour capacity over the standard "D" Line. Refer to Table #2 of Selector Guide for "D" series to Max Power series cross reference table.

EAST PENN manufacturing co., inc.

Lyon Station, PA 19536-0147 • Phone: 610-682-6361 • Fax: 610-682-4212
www.dekabatteries.com • e-mail: epmmotve@eastpenn-deka.com

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are $\pm 1/16"$. Battery weights may vary $\pm 5\%$. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.