



INDUSTRIAL BATTERIES

BARRETT

WALKIE, RIDER/WALKIE, TOW TRACTORS

| Truck Model and Maximum Battery Size (Inches) | Volt | Battery Type | Capacity 6 Hr. Rate | | AH/ Pos. Plate | IST Tray No. | Battery Dimensions (in.) | | | Approx. Serv. Wt. (lbs.) | Cover | | Leads Length | | Standard Conn. |
|--|------|--------------|---------------------|------|----------------|--------------|--------------------------|---------|----------|--------------------------|-------|----|--------------|-------|----------------|
| | | | KWH | A.H. | | | Length X | Width Y | Height Z | | Yes | No | Pos. | (in.) | |
| PG60, PG80, PGK60, PGK80 | 12 | 6-D100-13 | 6.98 | 600 | 100 | 1091 | 30.5 | 7.75 | 26.1875 | 613 | X | | B | 20 | SB6325 |
| STG40, STG60, WC20 | 12 | 6-D125-13 | 8.73 | 750 | 125 | 1092 | 30.5 | 7.75 | 31.0625 | 750 | X | | B | 20 | SB6325 |
| WC30, WC40, WP40, WP60 | 12 | 6-D85-13 | 5.94 | 510 | 85 | 1002 | 31.1875 | 7.75 | 23.1875 | 540 | X | | B | 20 | SB6325 |
| WP80, WRP40, WRP60 | 12 | 6-D85-13 | 5.94 | 510 | 85 | 1088 | 30.5 | 7.75 | 23.1875 | 538 | X | | B | 20 | SB6325 |
| WRP80, WS30, WS40, WTT | 12 | 6-H120-13 | 8.38 | 720 | 120 | 1092 | 30.5 | 7.75 | 31.0625 | 743 | X | | B | 20 | SB6325 |
| 32 x 8 x Open | 12 | 6-H80-13 | 5.59 | 480 | 80 | 1002 | 31.1875 | 7.75 | 23.1875 | 518 | X | | B | 20 | SB6325 |
| | 12 | 6-H80-13 | 5.59 | 480 | 80 | 1088 | 30.5 | 7.75 | 23.1875 | 516 | X | | B | 20 | SB6325 |
| | 12 | 6-P140-13 | 9.78 | 840 | 140 | 1092 | 30.5 | 7.75 | 31.0625 | 758 | X | | B | 20 | SB6325 |
| | 12 | 6-P95-13 | 6.63 | 570 | 95 | 1002 | 31.1875 | 7.75 | 23.1875 | 545 | X | | B | 20 | SB6325 |
| | 12 | 6-P95-13 | 6.63 | 570 | 95 | 1088 | 30.5 | 7.75 | 23.1875 | 543 | X | | B | 20 | SB6325 |
| WC20, WC30, WC40, WP40 WP60, WP80, WRP40 WRP60, WRP80, WS30 WS40, WTT 32 x 13.5 x Open | 12 | 6-D160-15 | 13.04 | 1120 | 160 | 1199 | 26.5625 | 11.875 | 31.125 | 1192 | X | | B | 20 | SB6325 |
| TTG10, TTG15, TTG20 | 12 | 6-D100-13 | 6.98 | 600 | 100 | 1091 | 30.5 | 7.75 | 26.1875 | 613 | X | | B | 20 | SB6325 |
| TTG25, TTG30, TTG40 | 12 | 6-D125-13 | 8.73 | 750 | 125 | 1092 | 30.5 | 7.75 | 31.0625 | 750 | X | | B | 20 | SB6325 |
| 31.25 x 8.125 x Open | 12 | 6-D85-13 | 5.94 | 510 | 85 | 1088 | 30.5 | 7.75 | 23.1875 | 538 | X | | B | 20 | SB6325 |
| | 12 | 6-H120-13 | 8.38 | 720 | 120 | 1092 | 30.5 | 7.75 | 31.0625 | 743 | X | | B | 20 | SB6325 |
| | 12 | 6-H80-13 | 5.59 | 480 | 80 | 1088 | 30.5 | 7.75 | 23.1875 | 516 | X | | B | 20 | SB6325 |
| | 12 | 6-P140-13 | 9.78 | 840 | 140 | 1092 | 30.5 | 7.75 | 31.0625 | 758 | X | | B | 20 | SB6325 |
| | 12 | 6-P95-13 | 6.63 | 570 | 95 | 1088 | 30.5 | 7.75 | 23.1875 | 543 | X | | B | 20 | SB6325 |

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE, RIDER/WALKIE, TOW TRACTORS (continued)

| Truck Model and Maximum Battery Size (Inches) | Volt | Battery Type | Capacity | | AH/ Pos. Plate | IST Tray No. | Battery Dimensions (in.) | | | Approx. Serv. Wt. (lbs.) | Cover | | Leads | | Standard Conn. | |
|--|-----------|-----------------|-------------------|-------|----------------------|--------------------|--------------------------|------------|-------------|--------------------------------|-------|----|-------|-----------------|-------------------|--------|
| | | | 6 Hr. Rate KWH | A.H. | | | Length X | Width Y | Height Z | | Yes | No | Pos. | Length (in.) | | |
| WC20, WC30, WC40, WP40 WP60, WP80, WS30, WS40 32 x 8 x Open | 24 | 12-D100-5 | cm | 4.66 | 200 | 100 | 3757 | 29.375 | 6.4375 | 26.1875 | 513 | X | | B | 24 | SB6325 |
| | 24 | 12-D100-5 | | 4.66 | 200 | 100 | 3209 | 24.625 | 6.4375 | 26.1875 | 474 | X | | B | 20 | SB6325 |
| | 24 | 12-D125-5 | | 5.82 | 250 | 125 | 3085 | 24.5625 | 6.5 | 31.0625 | 574 | X | | B | 20 | SB6325 |
| | 24 | 12-P140-5 | | 6.52 | 280 | 140 | 3085 | 24.5625 | 6.5 | 31.0625 | 580 | X | | B | 20 | SB6325 |
| EWP40 29 x 8.75 x 26.5 | 24 | 12-D100-5 | cm | 4.66 | 200 | 100 | 3526 | 24.25 | 8.3125 | 26.1875 | 514 | X | | B | 24 | SB6325 |
| | 24 | 12-D100-7 | | 6.98 | 300 | 100 | 3523 | 29 | 8.5625 | 26.1875 | 676 | X | | B | 20 | SB6325 |
| | 24 | 12-D100-7 | | 6.98 | 300 | 100 | 3123 | 25.3125 | 8.5625 | 26.1875 | 649 | X | | B | 20 | SB6325 |
| | 24 | 12-D85-7 | | 5.94 | 255 | 85 | 3042 | 25.25 | 8.5625 | 23.1875 | 567 | X | | B | 20 | SB6325 |
| | 24 | 12-H80-7 | | 5.59 | 240 | 80 | 3042 | 25.25 | 8.5625 | 23.1875 | 544 | X | | B | 20 | SB6325 |
| | 24 | 12-P95-7 | | 6.63 | 285 | 95 | 3042 | 25.25 | 8.5625 | 23.1875 | 573 | X | | B | 20 | SB6325 |
| PG60, PG80, PGX60, PGX80 SGX-1 40, SGX-1 60 SGX-1 80, SGX-1-24 SGX-1-24-F, SGX-1-24D SGX-1-24D-F, WC30, WC40 WRP40, WRP60, WRP80 WTT 32 x 13 x Open | 24 | 12-D100-11 | cm | 11.64 | 500 | 100 | 3539 | 31.375 | 12.875 | 26.25 | 1068 | X | | B | 30 | SB6325 |
| | 24 | 12-D85-11 | cm | 9.89 | 425 | 85 | 3163 | 31.375 | 12.875 | 23.25 | 965 | X | | B | 30 | SB6325 |
| | 24 | 12-H80-11 | cm | 9.31 | 400 | 80 | 3163 | 31.375 | 12.875 | 23.25 | 926 | X | | B | 30 | SB6325 |
| | 24 | 12-P95-11 | cm | 11.06 | 475 | 95 | 3163 | 31.375 | 12.875 | 23.25 | 975 | X | | B | 30 | SB6325 |
| | 24 | 12-D100-13 | | 13.97 | 600 | 100 | 3015 | 30.5625 | 12.75 | 26.25 | 1185 | X | | B | 20 | SB6325 |
| | 24 | 12-D125-13 | | 17.46 | 750 | 125 | 3008 | 30.5625 | 12.75 | 31.125 | 1455 | X | | B | 20 | SB6325 |
| | 24 | 12-D85-13 | | 11.87 | 510 | 85 | 3019 | 30.5625 | 12.75 | 23.25 | 1049 | X | | B | 20 | SB6325 |
| | 24 | 12-H120-13 | | 16.76 | 720 | 120 | 3008 | 30.5625 | 12.75 | 31.125 | 1440 | X | | B | 20 | SB6325 |
| | 24 | 12-H80-13 | | 11.17 | 480 | 80 | 3019 | 30.5625 | 12.75 | 23.25 | 1007 | X | | B | 20 | SB6325 |
| | 24 | 12-P140-13 | | 19.56 | 840 | 140 | 3008 | 30.5625 | 12.75 | 31.125 | 1470 | X | | B | 20 | SB6325 |
| 24 | 12-P95-13 | | 13.27 | 570 | 95 | 3019 | 30.5625 | 12.75 | 23.25 | 1059 | X | | B | 20 | SB6325 | |
| DG, DG-24, DG-24-D 31.75 x 13.125 x 23.5 | 24 | 12-D85-11 | cm | 9.89 | 425 | 85 | 3163 | 31.375 | 12.875 | 23.25 | 965 | X | | B | 30 | SB6325 |
| | 24 | 12-H80-11 | cm | 9.31 | 400 | 80 | 3163 | 31.375 | 12.875 | 23.25 | 926 | X | | B | 30 | SB6325 |
| | 24 | 12-P95-11 | cm | 11.06 | 475 | 95 | 3163 | 31.375 | 12.875 | 23.25 | 975 | X | | B | 30 | SB6325 |
| | 24 | 12-D85-13 | | 11.87 | 510 | 85 | 3019 | 30.5625 | 12.75 | 23.25 | 1049 | X | | B | 20 | SB6325 |
| | 24 | 12-H80-13 | | 11.17 | 480 | 80 | 3019 | 30.5625 | 12.75 | 23.25 | 1007 | X | | B | 20 | SB6325 |
| | 24 | 12-P95-13 | | 13.27 | 570 | 95 | 3019 | 30.5625 | 12.75 | 23.25 | 1059 | X | | B | 20 | SB6325 |
| SG, WSR-30 32.25 x 13.25 x Open | 24 | 12-D100-11 | cm | 11.64 | 500 | 100 | 3539 | 31.375 | 12.875 | 26.25 | 1068 | X | | B | 30 | SB6329 |
| | 24 | 12-D100-13 | | 13.97 | 600 | 100 | 3015 | 30.5625 | 12.75 | 26.25 | 1185 | X | | B | 20 | SB6329 |
| | 24 | 12-D125-13 | | 17.46 | 750 | 125 | 3008 | 30.5625 | 12.75 | 31.125 | 1455 | X | | B | 20 | SB6329 |
| | 24 | 12-D85-13 | | 11.87 | 510 | 85 | 3019 | 30.5625 | 12.75 | 23.25 | 1049 | X | | B | 20 | SB6329 |
| | 24 | 12-H120-13 | | 16.76 | 720 | 120 | 3008 | 30.5625 | 12.75 | 31.125 | 1440 | X | | B | 20 | SB6329 |
| | 24 | 12-H80-13 | | 11.17 | 480 | 80 | 3019 | 30.5625 | 12.75 | 23.25 | 1007 | X | | B | 20 | SB6329 |
| | 24 | 12-P140-13 | | 19.56 | 840 | 140 | 3008 | 30.5625 | 12.75 | 31.125 | 1470 | X | | B | 20 | SB6329 |
| | 24 | 12-P95-13 | | 13.27 | 570 | 95 | 3019 | 30.5625 | 12.75 | 23.25 | 1059 | X | | B | 20 | SB6329 |

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE, RIDER/WALKIE, TOW TRACTORS (continued)

| Truck Model and Maximum Battery Size (Inches) | Volt | Battery Type | Capacity | | AH/ Pos. Plate | IST Tray No. | Battery Dimensions (in.) | | | Approx. Serv. Wt. (lbs.) | Cover | | Leads | | Standard Conn. |
|---|------|-----------------|-------------------|------|----------------------|--------------------|--------------------------|------------|-------------|--------------------------------|-------|----|----------------------|----|-------------------|
| | | | 6 Hr. Rate KWH | A.H. | | | Length X | Width Y | Height Z | | Yes | No | Length Pos. (in.) | | |
| EWS-20, EWS-25 27.375 x 9 x Open | 24 | 12-D100-7 | 6.98 | 300 | 100 | 3123 | 25.3125 | 8.5625 | 26.1875 | 649 | X | | B | 15 | SB6329 |
| | 24 | 12-D125-7 | 8.73 | 375 | 125 | 3329 | 25.3125 | 8.5625 | 31.0625 | 792 | X | | B | 15 | SB6329 |
| | 24 | 12-D85-7 | 5.94 | 255 | 85 | 3042 | 25.25 | 8.5625 | 23.1875 | 567 | X | | B | 15 | SB6329 |
| | 24 | 12-H120-7 | 8.38 | 360 | 120 | 3329 | 25.3125 | 8.5625 | 31.0625 | 784 | X | | B | 15 | SB6329 |
| | 24 | 12-H80-7 | 5.59 | 240 | 80 | 3042 | 25.25 | 8.5625 | 23.1875 | 544 | X | | B | 15 | SB6329 |
| | 24 | 12-P140-7 | 9.78 | 420 | 140 | 3329 | 25.3125 | 8.5625 | 31.0625 | 800 | X | | B | 15 | SB6329 |
| | 24 | 12-P95-7 | 6.63 | 285 | 95 | 3042 | 25.25 | 8.5625 | 23.1875 | 573 | X | | B | 15 | SB6329 |
| SGB200, SGB60, SGB80 See Note A 31 x 13.5 x 31 | 24 | 12-D85-13 | 11.87 | 510 | 85 | 3019 | 30.5625 | 12.75 | 23.25 | 1049 | X | | B | 20 | SB6329 |
| | 24 | 12-H80-13 | 11.17 | 480 | 80 | 3019 | 30.5625 | 12.75 | 23.25 | 1007 | X | | B | 20 | SB6329 |
| | 24 | 12-P95-13 | 13.27 | 570 | 95 | 3019 | 30.5625 | 12.75 | 23.25 | 1059 | X | | B | 20 | SB6329 |
| SGB200, SGB60, SGB80 32 x 13.5 x 31 | 24 | 12-D85-13 | 11.87 | 510 | 85 | 3019 | 30.5625 | 12.75 | 23.25 | 1049 | X | | B | 20 | SB6329 |
| | 24 | 12-H80-13 | 11.17 | 480 | 80 | 3019 | 30.5625 | 12.75 | 23.25 | 1007 | X | | B | 20 | SB6329 |
| | 24 | 12-P95-13 | 13.27 | 570 | 95 | 3019 | 30.5625 | 12.75 | 23.25 | 1059 | X | | B | 20 | SB6329 |
| UNICAR 140L 32.75 x 13.5 x 25.6875 | 24 | 12-D85-13 | 11.87 | 510 | 85 | 3017 | 31.25 | 12.875 | 22.625 | | | X | B | 26 | SB6325 |
| | 24 | 12-H80-13 | 11.17 | 480 | 80 | 3017 | 31.25 | 12.875 | 22.625 | | | X | B | 26 | SB6325 |
| | 24 | 12-P95-13 | 13.27 | 570 | 95 | 3017 | 31.25 | 12.875 | 22.625 | | | X | B | 26 | SB6325 |
| UNICAR 140L 38 x 13.5 x 25.625 Optional Compartment | 24 | 12-D85-13 | 11.87 | 510 | 85 | 3159 | 35.5625 | 11.5625 | 22.625 | 1034 | | X | B | 26 | SB6325 |
| | 24 | 12-H80-13 | 11.17 | 480 | 80 | 3159 | 35.5625 | 11.5625 | 22.625 | 993 | | X | B | 26 | SB6325 |
| | 24 | 12-P95-13 | 13.27 | 570 | 95 | 3159 | 35.5625 | 11.5625 | 22.625 | 1044 | | X | B | 26 | SB6325 |
| | 24 | 12-D85-15 | 13.85 | 595 | 85 | 3056 | 35.0625 | 12.875 | 22.625 | 1178 | | X | B | 26 | SB6325 |
| | 24 | 12-H80-15 | 13.04 | 560 | 80 | 3056 | 35.0625 | 12.875 | 22.625 | 1131 | | X | B | 26 | SB6325 |
| | 24 | 12-P95-15 | 15.48 | 665 | 95 | 3056 | 35.0625 | 12.875 | 22.625 | 1190 | | X | B | 26 | SB6325 |

cm - Charge-Mate includes on board charger.

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

Note A - Battery compartment dimensions allow for optional battery gate.

STANDUP RIDERS

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are $\pm 1/16"$. Battery weights may vary $\pm 5\%$. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

STANDUP RIDERS

| Truck Model and Maximum Battery Size (Inches) | Volt | Battery Type | Capacity | | AH/ Pos. Plate | IST Tray No. | Battery Dimensions (in.) | | | Approx. Serv. Wt. (lbs.) | Cover | | Leads | | Standard Conn. |
|---|------|-----------------|-------------------|------|----------------------|--------------------|--------------------------|------------|-------------|--------------------------------|-------|----|----------------------|----|-------------------|
| | | | 6 Hr. Rate KWH | A.H. | | | Length X | Width Y | Height Z | | Yes | No | Length Pos. (in.) | | |
| RET20, RET25, RET30, RST30 | 24 | 12-D100-11 | 11.64 | 500 | 100 | 3539 | 31.375 | 12.875 | 26.25 | 1068 | X | | B | 30 | SB6325 |
| RST40 | 24 | 12-D100-13 | 13.97 | 600 | 100 | 3015 | 30.5625 | 12.75 | 26.25 | 1185 | X | | B | 25 | SB6325 |
| 32 x 13 x Open | 24 | 12-D125-13 | 17.46 | 750 | 125 | 3008 | 30.5625 | 12.75 | 31.125 | 1455 | X | | B | 25 | SB6325 |
| | 24 | 12-D85-13 | 11.87 | 510 | 85 | 3019 | 30.5625 | 12.75 | 23.25 | 1049 | X | | B | 25 | SB6325 |
| | 24 | 12-H120-13 | 16.76 | 720 | 120 | 3008 | 30.5625 | 12.75 | 31.125 | 1440 | X | | B | 25 | SB6325 |
| | 24 | 12-H80-13 | 11.17 | 480 | 80 | 3019 | 30.5625 | 12.75 | 23.25 | 1007 | X | | B | 25 | SB6325 |
| | 24 | 12-P140-13 | 19.56 | 840 | 140 | 3008 | 30.5625 | 12.75 | 31.125 | 1470 | X | | B | 25 | SB6325 |
| | 24 | 12-P95-13 | 13.27 | 570 | 95 | 3019 | 30.5625 | 12.75 | 23.25 | 1059 | X | | B | 25 | SB6325 |
| RRT-130, RRT-134, RRT-140 | 24 | 12-D160-11 | 18.62 | 800 | 160 | 3764 | 36.0625 | 14 | 30.5 | 1699 | | X | B | 20 | SB6322 |
| RST-140, RST-150 | 24 | 12-D125-17 | 23.28 | 1000 | 125 | 3127 | 38.1875 | 13.5 | 30.5625 | 1944 | | X | B | 20 | SB6322 |
| 38.75 x 14.5 x 32 | 24 | 12-H120-17 | 22.35 | 960 | 120 | 3127 | 38.1875 | 13.5 | 30.5625 | 1925 | | X | B | 20 | SB6322 |
| | 24 | 12-P140-17 | 26.07 | 1120 | 140 | 3127 | 38.1875 | 13.5 | 30.5625 | 1963 | | X | B | 20 | SB6322 |
| RRT-130, RRT-134 | 36 | 18-D125-11 | 21.83 | 625 | 125 | 6016 | 37.8125 | 13.3125 | 30.5625 | 1848 | | X | B | 20 | SB6320 |
| RRT-140, RST-140 | 36 | 18-H120-11 | 20.95 | 600 | 120 | 6016 | 37.8125 | 13.3125 | 30.5625 | 1830 | | X | B | 20 | SB6320 |
| RST-150 | 36 | 18-P140-11 | 24.44 | 700 | 140 | 6016 | 37.8125 | 13.3125 | 30.5625 | 1866 | | X | B | 20 | SB6320 |
| 38.75 x 14.5 x 32 | | | | | | | | | | | | | | | |
| RRT-130, RRT-134, RRT-140 | 24 | 12-D160-13 | 22.35 | 960 | 160 | 3049 | 35.25 | 15.5625 | 30.5625 | 1985 | | X | B | 20 | SB6322 |
| RST-140, RST-150 | 24 | 12-D125-17 | 23.28 | 1000 | 125 | 3127 | 38.1875 | 13.5 | 30.5625 | 1944 | | X | B | 20 | SB6322 |
| 38.75 x 16.5 x 32 | 24 | 12-H120-17 | 22.35 | 960 | 120 | 3127 | 38.1875 | 13.5 | 30.5625 | 1925 | | X | B | 20 | SB6322 |
| | 24 | 12-P140-17 | 26.07 | 1120 | 140 | 3127 | 38.1875 | 13.5 | 30.5625 | 1963 | | X | B | 20 | SB6322 |
| RRT-130, RRT-134 | 36 | 18-D125-13 | 26.19 | 750 | 125 | 6005 | 37.8125 | 15.5625 | 30.5625 | 2168 | | X | B | 20 | SB6320 |
| RRT-140, RST-140 | 36 | 18-H120-13 | 25.14 | 720 | 120 | 6005 | 37.8125 | 15.5625 | 30.5625 | 2146 | | X | B | 20 | SB6320 |
| RST-150 | 36 | 18-P140-13 | 29.33 | 840 | 140 | 6005 | 37.8125 | 15.5625 | 30.5625 | 2190 | | X | B | 20 | SB6320 |
| 38.75 x 16.5 x 32 | | | | | | | | | | | | | | | |
| RRT-140, RRT-40, RRT-DR | 36 | 18-D125-17 | 34.92 | 1000 | 125 | 6069 | 38.1875 | 20.0625 | 30.5625 | 2834 | | X | B | 20 | SB6320 |
| 38.75 x 21.25 x 32 | 36 | 18-H120-17 | 33.52 | 960 | 120 | 6069 | 38.1875 | 20.0625 | 30.5625 | 2806 | | X | B | 20 | SB6320 |
| | 36 | 18-P140-17 | 39.11 | 1120 | 140 | 6069 | 38.1875 | 20.0625 | 30.5625 | 2862 | | X | B | 20 | SB6320 |
| OSB25, OSB30S | 36 | 18-D125-11 | 21.83 | 625 | 125 | 6016 | 37.8125 | 13.3125 | 30.5625 | 1848 | | X | D | 12 | SB6320 |
| 38.75 x 13.875 x 31.5 | 36 | 18-H120-11 | 20.95 | 600 | 120 | 6016 | 37.8125 | 13.3125 | 30.5625 | 1830 | | X | D | 12 | SB6320 |
| | 36 | 18-P140-11 | 24.44 | 700 | 140 | 6016 | 37.8125 | 13.3125 | 30.5625 | 1866 | | X | D | 12 | SB6320 |

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

STANDUP RIDERS (continued)

| Truck Model and Maximum Battery Size (Inches) | Volt | Battery Type | Capacity 6 Hr. Rate | | AH/ Pos. Plate | IST Tray No. | Battery Dimensions (in.) | | | Approx. Serv. Wt. (lbs.) | Cover | | Leads Length | | Standard Conn. |
|---|------|-----------------|------------------------|------|----------------------|--------------------|--------------------------|------------|-------------|--------------------------------|-------|----|-----------------|-------|-------------------|
| | | | KWH | A.H. | | | Length X | Width Y | Height Z | | Yes | No | Pos. | (in.) | |
| OSB30 38.75 x 16.125 x 31.5 | 36 | 18-D125-13 | 26.19 | 750 | 125 | 6005 | 37.8125 | 15.5625 | 30.5625 | 2168 | | X | D | 12 | SB6320 |
| | 36 | 18-H120-13 | 25.14 | 720 | 120 | 6005 | 37.8125 | 15.5625 | 30.5625 | 2146 | | X | D | 12 | SB6320 |
| | 36 | 18-P140-13 | 29.33 | 840 | 140 | 6005 | 37.8125 | 15.5625 | 30.5625 | 2190 | | X | D | 12 | SB6320 |
| OSB35 38.75 x 18.375 x 31.5 | 36 | 18-D125-15 | 30.56 | 875 | 125 | 6045 | 38.1875 | 17.8125 | 30.5625 | 2486 | | X | D | 12 | SB6320 |
| | 36 | 18-H120-15 | 29.33 | 840 | 120 | 6045 | 38.1875 | 17.8125 | 30.5625 | 2461 | | X | D | 12 | SB6320 |
| | 36 | 18-P140-15 | 34.22 | 980 | 140 | 6045 | 38.1875 | 17.8125 | 30.5625 | 2511 | | X | D | 12 | SB6320 |
| OSB40, OSB45, OSB50 38.75 x 20.75 x 31.5 | 36 | 18-D125-17 | 34.92 | 1000 | 125 | 6069 | 38.1875 | 20.0625 | 30.5625 | 2834 | | X | D | 12 | SB6320 |
| | 36 | 18-H120-17 | 33.52 | 960 | 120 | 6069 | 38.1875 | 20.0625 | 30.5625 | 2806 | | X | D | 12 | SB6320 |
| | 36 | 18-P140-17 | 39.11 | 1120 | 140 | 6069 | 38.1875 | 20.0625 | 30.5625 | 2862 | | X | D | 12 | SB6320 |
| ORB35, ORB40 38.75 x 13.875 x 32 | 24 | 12-D125-17 | 23.28 | 1000 | 125 | 3127 | 38.1875 | 13.5 | 30.5625 | 1944 | | X | B | 14 | SB6320 |
| | 24 | 12-H120-17 | 22.35 | 960 | 120 | 3127 | 38.1875 | 13.5 | 30.5625 | 1925 | | X | B | 14 | SB6320 |
| | 24 | 12-P140-17 | 26.07 | 1120 | 140 | 3127 | 38.1875 | 13.5 | 30.5625 | 1963 | | X | B | 14 | SB6320 |
| ORB35, ORB40 38.75 x 13.875 x 32 | 36 | 18-D125-11 | 21.83 | 625 | 125 | 6016 | 37.8125 | 13.3125 | 30.5625 | 1848 | | X | B | 14 | SB6320 |
| | 36 | 18-H120-11 | 20.95 | 600 | 120 | 6016 | 37.8125 | 13.3125 | 30.5625 | 1830 | | X | B | 14 | SB6320 |
| | 36 | 18-P140-11 | 24.44 | 700 | 140 | 6016 | 37.8125 | 13.3125 | 30.5625 | 1866 | | X | B | 14 | SB6320 |
| ORB35, ORB40 Optional Compartment 38.75 x 16.125 x 32 | 24 | 12-D125-19 | 26.19 | 1125 | 125 | 3134 | 38.1875 | 15 | 30.5625 | 2126 | | X | B | 20 | SB6320 |
| | 24 | 12-H120-19 | 25.14 | 1080 | 120 | 3134 | 38.1875 | 15 | 30.5625 | 2105 | | X | B | 20 | SB6320 |
| | 24 | 12-P140-19 | 29.33 | 1260 | 140 | 3134 | 38.1875 | 15 | 30.5625 | 2147 | | X | B | 20 | SB6320 |
| ORB35, ORB40 Optional Compartment 38.75 x 16.125 x 32 | 36 | 18-D125-13 | 26.19 | 750 | 125 | 6005 | 37.8125 | 15.5625 | 30.5625 | 2168 | | X | B | 20 | SB6320 |
| | 36 | 18-H120-13 | 25.14 | 720 | 120 | 6005 | 37.8125 | 15.5625 | 30.5625 | 2146 | | X | B | 20 | SB6320 |
| | 36 | 18-P140-13 | 29.33 | 840 | 140 | 6005 | 37.8125 | 15.5625 | 30.5625 | 2190 | | X | B | 20 | SB6320 |
| ORB30, ORB40 38.75 x 18.5 x 32 | 36 | 18-D125-15 | 30.56 | 875 | 125 | 6045 | 38.1875 | 17.8125 | 30.5625 | 2486 | | X | B | 20 | SB6320 |
| | 36 | 18-H120-15 | 29.33 | 840 | 120 | 6045 | 38.1875 | 17.8125 | 30.5625 | 2461 | | X | B | 20 | SB6320 |
| | 36 | 18-P140-15 | 34.22 | 980 | 140 | 6045 | 38.1875 | 17.8125 | 30.5625 | 2511 | | X | B | 20 | SB6320 |
| ORB45, ORB30D Optional Compartment 38.75 x 21 x 32 | 36 | 18-D125-17 | 34.92 | 1000 | 125 | 6069 | 38.1875 | 20.0625 | 30.5625 | 2834 | | X | B | 20 | SB6320 |
| | 36 | 18-H120-17 | 33.52 | 960 | 120 | 6069 | 38.1875 | 20.0625 | 30.5625 | 2806 | | X | B | 20 | SB6320 |
| | 36 | 18-P140-17 | 39.11 | 1120 | 140 | 6069 | 38.1875 | 20.0625 | 30.5625 | 2862 | | X | B | 20 | SB6320 |

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

STANDUP RIDERS (continued)

| Truck Model and Maximum Battery Size (Inches) | Volt | Battery Type | Capacity 6 Hr. Rate | | AH/ Pos. Plate | IST Tray No. | Battery Dimensions (in.) | | | Approx. Serv. Wt. (lbs.) | Cover | | Leads Length | | Standard Conn. |
|--|------|-----------------|------------------------|------|----------------------|--------------------|--------------------------|------------|-------------|--------------------------------|-------|----|-----------------|-------|-------------------|
| | | | KWH | A.H. | | | Length X | Width Y | Height Z | | Yes | No | Pos. | (in.) | |
| RR35, RR30D, RR45, RS40 RS50 38.75 x 16.375 x 32 Min. Battery Wt. - 2000 lbs. | 24 | 12-D160-13 sp | 22.35 | 960 | 160 | 3780 | 37.875 | 15.5625 | 30.5625 | 2113 | | X | C | 15 | SB6322 |
| RR35 Optional Compartment 38.75 x 14.375 x 32 | 24 | 12-D160-11 | 18.62 | 800 | 160 | 3577 | 35.0625 | 13.1875 | 30.5 | 1693 | | X | C | 15 | SB6322 |
| RR35 Optional Compartment 38.75 x 14.375 x 32 | 36 | 18-D125-11 | 21.83 | 625 | 125 | 6016 | 37.8125 | 13.3125 | 30.5625 | 1848 | | X | C | 15 | SB6322 |
| | 36 | 18-H120-11 | 20.95 | 600 | 120 | 6016 | 37.8125 | 13.3125 | 30.5625 | 1830 | | X | C | 15 | SB6322 |
| | 36 | 18-P140-11 | 24.44 | 700 | 140 | 6016 | 37.8125 | 13.3125 | 30.5625 | 1866 | | X | C | 15 | SB6322 |
| RR30D, RR35, RR45, RS40 RS50 38.75 x 16.375 x 32 | 36 | 18-D125-13 | 26.19 | 750 | 125 | 6005 | 37.8125 | 15.5625 | 30.5625 | 2168 | | X | C | 15 | SB6320 |
| | 36 | 18-H120-13 | 25.14 | 720 | 120 | 6005 | 37.8125 | 15.5625 | 30.5625 | 2146 | | X | C | 15 | SB6320 |
| | 36 | 18-P140-13 | 29.33 | 840 | 140 | 6005 | 37.8125 | 15.5625 | 30.5625 | 2190 | | X | C | 15 | SB6320 |
| RR45, RR30D Optional Compartment 38.75 x 20.875 x 32 | 36 | 18-D125-17 | 34.92 | 1000 | 125 | 6069 | 38.1875 | 20.0625 | 30.5625 | 2834 | | X | C | 15 | SB6320 |
| | 36 | 18-H120-17 | 33.52 | 960 | 120 | 6069 | 38.1875 | 20.0625 | 30.5625 | 2806 | | X | C | 15 | SB6320 |
| | 36 | 18-P140-17 | 39.11 | 1120 | 140 | 6069 | 38.1875 | 20.0625 | 30.5625 | 2862 | | X | C | 15 | SB6320 |
| RR45, RR30D Optional Compartment 38.75 x 20.875 x 32 | 36 | 18-D125-17 | 34.92 | 1000 | 125 | 6069 | 38.1875 | 20.0625 | 30.5625 | 2834 | | X | C | 15 | SB6320 |
| | 36 | 18-H120-17 | 33.52 | 960 | 120 | 6069 | 38.1875 | 20.0625 | 30.5625 | 2806 | | X | C | 15 | SB6320 |
| | 36 | 18-P140-17 | 39.11 | 1120 | 140 | 6069 | 38.1875 | 20.0625 | 30.5625 | 2862 | | X | C | 15 | SB6320 |

sp - Special tray IST3780 includes steel plates added for minimum weight requirement.
H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

ORDER SELECTORS

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are $\pm 1/16"$. Battery weights may vary $\pm 5\%$. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

ORDER SELECTORS

| Truck Model and Maximum Battery Size (Inches) | Volt | Battery Type | Capacity 6 Hr. Rate | | AH/ Pos. Plate | IST Tray No. | Battery Dimensions (in.) | | | Approx. Serv. Wt. (lbs.) | Cover | | Leads Length | | Standard Conn. |
|--|------|-----------------|------------------------|------|----------------------|--------------------|--------------------------|------------|-------------|--------------------------------|-------|----|-----------------|-------|-------------------|
| | | | KWH | A.H. | | | Length X | Width Y | Height Z | | Yes | No | Pos. | (in.) | |
| RCOS, RCOS3000 38.75 x 14.5 x 31.5 | 24 | 12-D160-11 | 18.62 | 800 | 160 | 3764 | 36.0625 | 14 | 30.5 | 1699 | | X | B | 20 | SB6322 |
| | 24 | 12-D160-11 | 18.62 | 800 | 160 | 3025 | 35.0625 | 13.1875 | 30.5 | 1647 | | X | B | 20 | SB6322 |
| | 24 | 12-D125-17 | 23.28 | 1000 | 125 | 3127 | 38.1875 | 13.5 | 30.5625 | 1944 | | X | B | 20 | SB6322 |
| | 24 | 12-H120-17 | 22.35 | 960 | 120 | 3127 | 38.1875 | 13.5 | 30.5625 | 1925 | | X | B | 20 | SB6322 |
| | 24 | 12-P140-17 | 26.07 | 1120 | 140 | 3127 | 38.1875 | 13.5 | 30.5625 | 1963 | | X | B | 20 | SB6322 |
| RCOS 30 32 x 13.375 x 31.125 | 24 | 12-D125-13 | 17.46 | 750 | 125 | 3008 | 30.5625 | 12.75 | 31.125 | 1455 | X | | B | 25 | SB6320 |
| | 24 | 12-H120-13 | 16.76 | 720 | 120 | 3008 | 30.5625 | 12.75 | 31.125 | 1440 | X | | B | 25 | SB6320 |
| | 24 | 12-P140-13 | 19.56 | 840 | 140 | 3008 | 30.5625 | 12.75 | 31.125 | 1470 | X | | B | 25 | SB6320 |
| RCS01 38.75 x 14.5 x 31.5625 | 24 | 12-D160-11 | 18.62 | 800 | 160 | 3764 | 36.0625 | 14 | 30.5 | 1699 | | X | B | 25 | SB6320 |
| | 24 | 12-D160-11 | 18.62 | 800 | 160 | 3025 | 35.0625 | 13.1875 | 30.5 | 1647 | | X | B | 25 | SB6320 |
| | 24 | 12-D125-15 | 20.37 | 875 | 125 | 3692 | 36.0625 | 14 | 30.5 | 1637 | | X | B | 25 | SB6320 |
| | 24 | 12-D125-15 | 20.37 | 875 | 125 | 3670 | 36.0625 | 14 | 30.5 | 1739 | | X | B | 25 | SB6320 |
| | 24 | 12-D125-15 | 20.37 | 875 | 125 | 3036 | 35.0625 | 12.875 | 30.5 | 1651 | | X | B | 25 | SB6320 |
| | 24 | 12-H120-15 | 19.56 | 840 | 120 | 3692 | 36.0625 | 14 | 30.5 | 1621 | | X | B | 25 | SB6320 |
| | 24 | 12-H120-15 | 19.56 | 840 | 120 | 3670 | 36.0625 | 14 | 30.5 | 1722 | | X | B | 25 | SB6320 |
| | 24 | 12-H120-15 | 19.56 | 840 | 120 | 3036 | 35.0625 | 12.875 | 30.5 | 1634 | | X | B | 25 | SB6320 |
| | 24 | 12-P140-15 | 22.81 | 980 | 140 | 3692 | 36.0625 | 14 | 30.5 | 1653 | | X | B | 25 | SB6320 |
| | 24 | 12-P140-15 | 22.81 | 980 | 140 | 3670 | 36.0625 | 14 | 30.5 | 1756 | | X | B | 25 | SB6320 |
| | 24 | 12-P140-15 | 22.81 | 980 | 140 | 3036 | 35.0625 | 12.875 | 30.5 | 1668 | | X | B | 25 | SB6320 |
| | 24 | 12-D125-17 | 23.28 | 1000 | 125 | 3127 | 38.1875 | 13.5 | 30.5625 | 1944 | | X | B | 25 | SB6320 |
| | 24 | 12-H120-17 | 22.35 | 960 | 120 | 3127 | 38.1875 | 13.5 | 30.5625 | 1925 | | X | B | 25 | SB6320 |
| | 24 | 12-P140-17 | 26.07 | 1120 | 140 | 3127 | 38.1875 | 13.5 | 30.5625 | 1963 | | X | B | 25 | SB6320 |
| GRCSS25, GRCSS30, RCSS25 RCSS30, RSSS 32.5 x 13.375 x Open | 24 | 12-D100-13 | 13.97 | 600 | 100 | 3015 | 30.5625 | 12.75 | 26.25 | 1185 | X | | B | 25 | SB6325 |
| | 24 | 12-D125-13 | 17.46 | 750 | 125 | 3008 | 30.5625 | 12.75 | 31.125 | 1455 | X | | B | 25 | SB6325 |
| | 24 | 12-D85-13 | 11.87 | 510 | 85 | 3019 | 30.5625 | 12.75 | 23.25 | 1049 | X | | B | 25 | SB6325 |
| | 24 | 12-H120-13 | 16.76 | 720 | 120 | 3008 | 30.5625 | 12.75 | 31.125 | 1440 | X | | B | 25 | SB6325 |
| | 24 | 12-H80-13 | 11.17 | 480 | 80 | 3019 | 30.5625 | 12.75 | 23.25 | 1007 | X | | B | 25 | SB6325 |
| | 24 | 12-P140-13 | 19.56 | 840 | 140 | 3008 | 30.5625 | 12.75 | 31.125 | 1470 | X | | B | 25 | SB6325 |
| | 24 | 12-P95-13 | 13.27 | 570 | 95 | 3019 | 30.5625 | 12.75 | 23.25 | 1059 | X | | B | 25 | SB6325 |
| RCOS, RCOS3000 38.75 x 14.5 x 31.5 | 36 | 18-D125-11 | 21.83 | 625 | 125 | 6782 | 38.0625 | 13.5625 | 30.5625 | 1887 | | X | B | 20 | SB6320 |
| | 36 | 18-D125-11 | 21.83 | 625 | 125 | 6016 | 37.8125 | 13.3125 | 30.5625 | 1848 | | X | B | 20 | SB6320 |
| | 36 | 18-H120-11 | 20.95 | 600 | 120 | 6782 | 38.0625 | 13.5625 | 30.5625 | 1868 | | X | B | 20 | SB6320 |
| | 36 | 18-H120-11 | 20.95 | 600 | 120 | 6016 | 37.8125 | 13.3125 | 30.5625 | 1830 | | X | B | 20 | SB6320 |
| | 36 | 18-P140-11 | 24.44 | 700 | 140 | 6782 | 38.0625 | 13.5625 | 30.5625 | 1906 | | X | B | 20 | SB6320 |
| | 36 | 18-P140-11 | 24.44 | 700 | 140 | 6016 | 37.8125 | 13.3125 | 30.5625 | 1866 | | X | B | 20 | SB6320 |

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

Some older models require SB6316 with 12 volt tap.
sp - IST3692 tray includes ribbed sides.
H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

Batteries listed are also available in the Max Power "P" Line which is a 10% increase of ampere hour capacity over the standard "D" Line. Refer to Table #2 of Selector Guide for "D" series to Max Power series cross reference table.

EAST PENN manufacturing co., inc.

Lyon Station, PA 19536-0147 • Phone: 610-682-6361 • Fax: 610-682-4212
www.dekabatteries.com • e-mail: epmmotve@eastpenn-deka.com

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are $\pm 1/16"$. Battery weights may vary $\pm 5\%$. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.