



INDUSTRIAL BATTERIES

DREXEL

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type		Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
				KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
FL40EX, FL60EX 37.625 x 27.375 x 25.25 Min. Battery Wt. - 2475lbs.	36	18-D85-19	EX	26.71	765	85	6205	37.0625	25.9375	24.125	2476	X		Mounted	N7869	
SL22ESS 27.375 x 20.5 x 27.625 Min. Battery Wt. - 1350 lbs.	24	12-D100-17		18.62	800	100	3190	26.5625	19.1875	25.625	1545		X	D	36	SB6320
SL22ESS 40.375 x 20.5 x 26 Min. Battery Wt. - 2050 lbs.	36	18-D100-17		27.94	800	100	6060	38.1875	20.0625	25.6875	2322		X	D	36	SB6320
SL33HP 39 x 26.375 x 26 Min. Battery Wt. - 2750 lbs.	36	18-D100-21		34.92	1000	100	6067	38.1875	24.5625	25.6875	2805		X	B	36	SB6320 w/919
SL44/3, SL44/4 39 x 27.125 x 26 Min. Battery Wt. - 3100 lbs.	36	18-D100-23		38.41	1100	100	6003	38.5625	26.9375	25.6875	3152		X	B	36	SB6320 w/919
SL44ESS, HP, SL55 39.25 x 30.5 x 23.75 Min. Battery Wt. - 2900 lbs.	36	18-D85-25		35.62	1020	85	6030	38.1875	29.1875	22.6875	2924		X	A	30	SB6320 w/919
	36	18-H80-25		33.52	960	80	6030	38.1875	29.1875	22.6875	2807		X	A	30	SB6320 w/919
	36	18-P95-25		39.81	1140	95	6030	38.1875	29.1875	22.6875	2953		X	A	30	SB6320 w/919
SL66, SL77, SL88 39.25 x 37.375 x 23.75 Min. Battery Wt. - 3700 lbs.	36	18-D85-31	sp	44.52	1275	85	6996	38.6875	35.9375	22.6875	3705		X	D	24	SB6320 w/919
	36	18-H80-31	sp	41.90	1200	80	6996	38.6875	35.9375	22.6875	3557		X	D	24	SB6320 w/919
	36	18-P95-31	sp	49.76	1425	95	6996	38.6875	35.9375	22.6875	3742		X	D	24	SB6320 w/919

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.		
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)			
SLT22 PRE 1993 39.75 x 21 x 27 Min. Battery Wt. - 2100 lbs.	36	18-D100-17	27.94	800	100	6060	38.1875	20.0625	25.6875	2322		X	D	36	SB6320	w/919	
SLT22, SLT30 after 1992 39.75 x 23.25 x 27 Min. Battery Wt. - 2100 lbs.	36	18-D100-19	31.43	900	100	6057	38.1875	22.3125	25.6875	2564		X	D	36	SB6320	w/919	
	36	18-D85-19	26.71	765	85	6041	38.1875	22.3125	22.6875	2242		X	D	36	SB6320	w/919	
	36	18-H80-19	25.14	720	80	6041	38.1875	22.3125	22.6875	2152		X	D	36	SB6320	w/919	
	36	18-P95-19	29.86	855	95	6041	38.1875	22.3125	22.6875	2264		X	D	36	SB6320	w/919	
SLT35, SLT30 38.625 x 21.75 x 27 Min. Battery Wt. - 2100 lbs.	36	18-D100-17	27.94	800	100	6060	38.1875	20.0625	25.6875	2322		X	D	36	SB6320	w/919	
MDR45 63.875 x 13.375 x 31.5 Min. Battery Wt. - 2420 lbs.	48	24-D125-13	34.92	750	125	7409	60.875	12.9375	31.4375	2959	X		B	18	SB6321		
	48	24-H120-13	33.52	720	120	7409	60.875	12.9375	31.4375	2929	X		B	18	SB6321		
	48	24-P140-13	39.11	840	140	7409	60.875	12.9375	31.4375	2989	X		B	18	SB6321		
MDR55 63.875 x 13.375 x 31.5 Min. Battery Wt. - 2620 lbs.	48	24-D125-13	34.92	750	125	7409	60.875	12.9375	31.4375	2959	X		B	18	SB6321		
	48	24-H120-13	33.52	720	120	7409	60.875	12.9375	31.4375	2929	X		B	18	SB6321		
	48	24-P140-13	39.11	840	140	7409	60.875	12.9375	31.4375	2989	X		B	18	SB6321		
MDR55 Optional Compartment 63.875 x 15.5 x 31.5 Min. Battery Wt. - 2620 lbs.	48	24-D125-13	34.92	750	125	7409	60.875	12.9375	31.4375	2959	X		B	18	SB6321		
	48	24-H120-13	33.52	720	120	7409	60.875	12.9375	31.4375	2929	X		B	18	SB6321		
	48	24-P140-13	39.11	840	140	7409	60.875	12.9375	31.4375	2989	X		B	18	SB6321		
LLH40, LLH70, LLH90 49.1875 x 18.25 x 31.1875 Min. Battery Wt. - 2500 lbs.	48	24-D125-11	sp	29.10	625	125	7420	49.1875	18.25	31.1875	2660	X		C	24	SB6321	w/919
	48	24-H120-11	sp	27.94	600	120	7420	49.1875	18.25	31.1875	2633	X		C	24	SB6321	w/919
	48	24-P140-11	sp	32.59	700	140	7420	49.1875	18.25	31.1875	2687	X		C	24	SB6321	w/919
DXR35-F, DXR35-S 47.6875 x 17.0625 x 31.8125 Min. Battery Wt. - 2425 lbs.	48	24-D125-11	29.10	625	125	7758	45.5	16.5	31.1875	2510	X		B	18	SB6321		
	48	24-H120-11	27.94	600	120	7758	45.5	16.5	31.1875	2485	X		B	18	SB6321		
	48	24-P140-11	32.59	700	140	7758	45.5	16.5	31.1875	2535	X		B	18	SB6321		
DXR35-F, DXR35-S DXR45-S, DXR55-S Optional Compartment 47.6875 x 11.3125 x 31.8125 Min. Battery Wt. - 1545 lbs.	48	24-D125-7	17.46	375	125	7759	47.3125	10.4375	31.125	1582	X		B	18	SB6321		
	48	24-H120-7	16.76	360	120	7759	47.3125	10.4375	31.125	1566	X		B	18	SB6321		
	48	24-P140-7	19.56	420	140	7759	47.3125	10.4375	31.125	1598	X		B	18	SB6321		

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
DXR35-F	48	24-D125-9	23.28	500	125	7525	47.4375	13.75	31.375	2170	X		B	18	SB6321
DXR35-S	48	24-H120-9	22.35	480	120	7525	47.4375	13.75	31.375	2148	X		B	18	SB6321
Optional Compartment 47.6875 x 14.875 x 31.8125 Min. Battery Wt. - 1985 lbs.	48	24-P140-9	26.07	560	140	7525	47.4375	13.75	31.375	2192	X		B	18	SB6321
DXR35-C	48	24-D125-9	23.28	500	125	7287	37.8125	14.5625	31.1875	2064	X		B	18	SB6321
41.8125 x 17.0625 x 31.8125	48	24-H120-9	22.35	480	120	7287	37.8125	14.5625	31.1875	2043	X		B	18	SB6321
Min. Battery Wt. - 1985 lbs.	48	24-P140-9	26.07	560	140	7287	37.8125	14.5625	31.1875	2085	X		B	18	SB6321
DXR35-C	48	24-D125-9	23.28	500	125	7760	40.25	13.75	31.1875	2031	X		B	18	SB6321
Optional Compartment	48	24-H120-9	22.35	480	120	7760	40.25	13.75	31.1875	2011	X		B	18	SB6321
41.8125 x 14.1875 x 31.8125 Min. Battery Wt. - 1545 lbs.	48	24-P140-9	26.07	560	140	7760	40.25	13.75	31.1875	2051	X		B	18	SB6321
DDXR45-S, DXR45-H	48	24-D125-11	29.10	625	125	7758	45.5	16.5	31.1875	2510	X		B	18	SB6321
DXR55-H/S	48	24-H120-11	27.94	600	120	7758	45.5	16.5	31.1875	2485	X		B	18	SB6321
47.75 x 17.0625 x 31.8125 Min. Battery Wt. - 2425 lbs.	48	24-P140-11	32.59	700	140	7758	45.5	16.5	31.1875	2535	X		B	18	SB6321
DXR45-H, DXR55-H/S	48	24-D125-15	40.74	875	125	7523	46.6875	19.3125	31.4375	3361	X		B	18	SB6321
47.75 x 19.8125 x 31.8125	48	24-H120-15	39.11	840	120	7523	46.6875	19.3125	31.4375	3327	X		B	18	SB6321
Min. Battery Wt. - 2865 lbs.	48	24-P140-15	45.63	980	140	7523	46.6875	19.3125	31.4375	3395	X		B	18	SB6321
DXR45-S, DXR45-H	48	24-D125-9	23.28	500	125	7525	47.4375	13.75	31.375	2170	X		B	18	SB6321
DXR55-S	48	24-H120-9	22.35	480	120	7525	47.4375	13.75	31.375	2148	X		B	18	SB6321
47.75 x 14.1875 x 31.8125 Min. Battery Wt. - 1985 lbs.	48	24-P140-9	26.07	560	140	7525	47.4375	13.75	31.375	2192	X		B	18	SB6321
DXT30	48	24-D125-11	29.10	625	125	7758	45.5	16.5	31.1875	2510	X		B	18	SB6321
48.25 x 16.875 x 31.5	48	24-H120-11	27.94	600	120	7758	45.5	16.5	31.1875	2485	X		B	18	SB6321
Min. Battery Wt. - 2470 lbs.	48	24-P140-11	32.59	700	140	7758	45.5	16.5	31.1875	2535	X		B	18	SB6321
SL50	48	24-D100-21	46.56	1000	100	7117	38.1875	32.6875	25.6875	3754		X	A	36	SB6321
38.625 x 33.5 x 25.75 Min. Battery Wt. - 3250 lbs.															
SL60, SL80	72	36-D85-19	53.43	765	85	8008	44.1875	38.1875	22.6875	4422		X	D	36	SB6343
45 x 39.625 x 23.5	72	36-H80-19	50.28	720	80	8008	44.1875	38.1875	22.6875	4245		X	D	36	SB6343
Min. Battery Wt. - 4300 lbs.	72	36-P95-19	59.71	855	95	8008	44.1875	38.1875	22.6875	4466		X	D	36	SB6343

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
SL120 45 x 39.75 x 22.75 Min. Battery Wt. - 2140 lbs. See Note A	72	18-D85-19	26.71 ea	765	85	6315	44.1875	19.3125	22.6875	2269		X	A	36	SB6320
	72	18-H80-19	25.14 ea	720	80	6315	44.1875	19.3125	22.6875	2178		X	A	36	SB6320
	72	18-P95-19	29.86 ea	855	95	6315	44.1875	19.3125	22.6875	2292		X	A	36	SB6320
SLF30 39.375 x 28.5 x 27.5 Min. Battery Wt. - 2650 lbs.	36	18-D100-23	38.41	1100	100	6140	38.1875	26.9375	25.6875	3095		X	B	24	SB6321
SLF30 39.375 x 28.5 x 27.5 Min. Battery Wt. - 2650 lbs.	48	24-D100-17	37.25	800	100	7086	38.1875	26.6875	25.6875	3112		X	B	24	SB6321
SLF40 39.375 x 33.5 x 27.5 Min. Battery Wt. - 2900 lbs.	36	18-D100-27	45.40	1300	100	6281	38.1875	31.4375	25.6875	3608		X	B	24	SB6321
SLF40 39.375 x 33.5 x 27.5 Min. Battery Wt. - 2900 lbs.	48	24-D100-19	41.90	900	100	7043	38.1875	29.6875	25.6875	3465		X	B	24	SB6321
SLT35HLC 38.625 x 26.5 x 27 Min. Battery Wt. - 2650 lbs.	48	24-D100-15	32.59	700	100	7135	38.1875	23.5625	25.6875	2670		X	D	36	SB6321

EX - Explosion-proof battery and tray design.

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

sp - Special tray IST6996 includes steel plates added for minimum weight requirement.

sp - Special L-shaped tray IST7420 includes locking feet, bobtail filler, inverted hinge, cover latches and handles.

Note A: 72 volt Model SL120 requires (2) 18 cell batteries.

Ea - KWH calculated for each 18 cell battery.

Batteries listed are also available in the Max Power "P" Line which is a 10% increase of ampere hour capacity over the standard "D" Line. Refer to Table #2 of Selector Guide for "D" series to Max Power series cross reference table.

EAST PENN manufacturing co., inc.

Lyon Station, PA 19536-0147 • Phone: 610-682-6361 • Fax: 610-682-4212
www.dekabatteries.com • e-mail: epmmotve@eastpenn-deka.com

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.