



INDUSTRIAL BATTERIES

DAEWOO/DOOSAN

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity 6 Hr. Rate		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
BC20 40.1875 x 30.5 x 23 Min. Battery Wt. - 2400 lbs.	36	18-D85-25	35.62	1020	85	6030	38.1875	29.1875	22.6875	2924		X	B	18	SB6320
	36	18-H80-25	33.52	960	80	6030	38.1875	29.1875	22.6875	2807		X	B	18	SB6320
	36	18-P95-25	39.81	1140	95	6030	38.1875	29.1875	22.6875	2953		X	B	18	SB6320
BC20 40.1875 x 30.5 x 23 Min. Battery Wt. - 2400 lbs.	48	24-D85-19	35.62	765	85	7003	38.1875	29.6875	22.6875	2994		X	B	18	SB6320
	48	24-H80-19	33.52	720	80	7003	38.1875	29.6875	22.6875	2874		X	B	18	SB6320
	48	24-P95-19	39.81	855	95	7003	38.1875	29.6875	22.6875	3024		X	B	18	SB6320
BC25 40.1875 x 34.375 x 23 Min. Battery Wt. - 2950 lbs.	36	18-D85-27	38.59	1105	85	6026	38.1875	31.4375	22.6875	3144		X	B	18	SB6320
	36	18-H80-27	36.32	1040	80	6026	38.1875	31.4375	22.6875	3018		X	B	18	SB6320
	36	18-P95-27	43.13	1235	95	6026	38.1875	31.4375	22.6875	3175		X	B	18	SB6320
BC25 40.1875 x 34.375 x 23 Min. Battery Wt. - 2950 lbs.	48	24-D85-21	39.58	850	85	7004	38.1875	32.6875	22.6875	3279		X	B	18	SB6320
	48	24-H80-21	37.25	800	80	7004	38.1875	32.6875	22.6875	3148		X	B	18	SB6320
	48	24-P95-21	44.23	950	95	7004	38.1875	32.6875	22.6875	3312		X	B	18	SB6320
BC30 40.1875 x 34.375 x 23 Min. Battery Wt. - 3060 lbs.	36	18-D85-29	41.55	1190	85	6021	38.1875	33.6875	22.6875	3394		X	B	18	SB6320
	36	18-H80-29	39.11	1120	80	6021	38.1875	33.6875	22.6875	3258		X	B	18	SB6320
	36	18-P95-29	46.44	1330	95	6021	38.1875	33.6875	22.6875	3428		X	B	18	SB6320
BC30 40.1875 x 34.375 x 23 Min. Battery Wt. - 3060 lbs.	48	24-D85-21	39.58	850	85	7004	38.1875	32.6875	22.6875	3279		X	B	18	SB6320
	48	24-H80-21	37.25	800	80	7004	38.1875	32.6875	22.6875	3148		X	B	18	SB6320
	48	24-P95-21	44.23	950	95	7004	38.1875	32.6875	22.6875	3312		X	B	18	SB6320
B20, B20S-2 45.5 x 41.3125 x 20.875 Min. Battery Wt. - 2447 lbs.	36	18-D65-33	36.32	1040	65	6273	38.1875	38.1875	20.0625	3286		X	B	18	SB6320

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
B20, B20S-2 45.5 x 41.3125 x 20.875 Min. Battery Wt. - 2430 lbs.	48	24-D65-29	42.37	910	65	7321	44.6875	38.1875	20.0625	3813		X	B	18	SB6320
B20S-2 45.5 x 41.3125 x 20.875 Min. Battery Wt. - 2430 lbs.	72	36-D65-17	36.32	520	65	8025	39.6875	38.1875	20.0625	3473		X	B	18	SB6320
B20S-2 45.5 x 41.3125 x 20.875 Min. Battery Wt. - 2430 lbs. NEW TRAY REQUIRED												X	B	18	SB6320
B25, B25S-2 45.5 x 41.3125 x 20.875 Min. Battery Wt. - 3250 lbs.	36	18-D65-33	36.32	1040	65	6273	38.1875	38.1875	20.0625	3286		X	B	18	SB6320
B25, B25S-2 45.5 x 41.3125 x 20.875 Min. Battery Wt. - 3250 lbs.	48	24-D65-29	42.37	910	65	7321	44.6875	38.1875	20.0625	3813		X	B	18	SB6320
B25S-2 45.5 x 41.3125 x 20.875 Min. Battery Wt. - 3250 lbs.	72	36-D65-17	36.32	520	65	8025	39.6875	38.1875	20.0625	3473		X	B	18	SB6320
B25S-2 45.5 x 41.3125 x 20.875 Min. Battery Wt. - 3250 lbs. NEW TRAY REQUIRED												X	B	18	SB6320
B30 49.1875 x 45.5 x 20.875 Min. Battery Wt. - 3425 lbs.	36	18-D65-33	36.32	1040	65	6273	38.1875	38.1875	20.0625	3286		X	B	18	SB6320
B30 49.1875 x 45.5 x 20.875 Min. Battery Wt. - 3425 lbs.	48	24-D65-31	45.40	975	65	7120	47.6875	38.1875	20.0625	4129		X	B	18	SB6320
B30S-2 49.1875 x 45.5 x 20.875 Min. Battery Wt. - 3350 lbs.	36	18-D65-33	36.32	1040	65	6555	40	40	20.0625	3486		X	B	18	SB6320
	36	18-D65-33	36.32	1040	65	6273	38.1875	38.1875	20.0625	3286 **		X	B	18	SB6320

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
B30S-2, B30S 49.1875 x 45.5 x 20.875 Min. Battery Wt. - 3350 lbs.	48	24-D65-31	45.40	975	65	7120	47.6875	38.1875	20.0625	4129		X	B	18	SB6320
B30S-2 49.1875 x 45.5 x 20.875 Min. Battery Wt. - 3350 lbs.	72	36-D65-17	36.32	520	65	8025	39.6875	38.1875	20.0625	3473		X	B	18	SB6320
B30S-2 49.1875 x 45.5 x 20.875 Min. Battery Wt. - 3350 lbs. NEW TRAY REQUIRED												X	B	18	SB6320
BC20S 40.1875 x 30.5 x 23.5625 Min. Battery Wt. - 2400 lbs.	36	18-D85-25	35.62	1020	85	6030	38.1875	29.1875	22.6875	2924		X	B	18	SB6320
	36	18-H80-25	33.52	960	80	6030	38.1875	29.1875	22.6875	2807		X	B	18	SB6320
	36	18-P95-25	39.81	1140	95	6030	38.1875	29.1875	22.6875	2953		X	B	18	SB6320
BC20S 40.1875 x 30.5 x 23.5625 Min. Battery Wt. - 2400 lbs.	48	24-D85-19	35.62	765	85	7003	38.1875	29.6875	22.6875	2994		X	B	18	SB6320
	48	24-H80-19	33.52	720	80	7003	38.1875	29.6875	22.6875	2874		X	B	18	SB6320
	48	24-P95-19	39.81	855	95	7003	38.1875	29.6875	22.6875	3024		X	B	18	SB6320
BC25S 40.1875 x 33.25 x 23.5625 Min. Battery Wt. - 2950 lbs.	36	18-D85-27	38.59	1105	85	6026	38.1875	31.4375	22.6875	3144		X	B	18	SB6320
	36	18-H80-27	36.32	1040	80	6026	38.1875	31.4375	22.6875	3018		X	B	18	SB6320
	36	18-P95-27	43.13	1235	95	6026	38.1875	31.4375	22.6875	3175		X	B	18	SB6320
BC25S 40.1875 x 33.25 x 23.5625 Min. Battery Wt. - 2950 lbs.	48	24-D85-21	39.58	850	85	7004	38.1875	32.6875	22.6875	3279		X	B	18	SB6320
	48	24-H80-21	37.25	800	80	7004	38.1875	32.6875	22.6875	3148		X	B	18	SB6320
	48	24-P95-21	44.23	950	95	7004	38.1875	32.6875	22.6875	3312		X	B	18	SB6320
BC30S, BC25SE 40.1875 x 34.125 x 23.5625 Min. Battery Wt. - 3060 lbs.	36	18-D85-29	41.55	1190	85	6021	38.1875	33.6875	22.6875	3394		X	B	18	SB6320
	36	18-H80-29	39.11	1120	80	6021	38.1875	33.6875	22.6875	3258		X	B	18	SB6320
	36	18-P95-29	46.44	1330	95	6021	38.1875	33.6875	22.6875	3428		X	B	18	SB6320
BC30S, BC25SE 40.1875 x 34.125 x 23.1875 Min. Battery Wt. - 3060 lbs.	48	24-D85-21	39.58	850	85	7004	38.1875	32.6875	22.6875	3279		X	B	18	SB6320
	48	24-H80-21	37.25	800	80	7004	38.1875	32.6875	22.6875	3148		X	B	18	SB6320
	48	24-P95-21	44.23	950	95	7004	38.1875	32.6875	22.6875	3312		X	B	18	SB6320
BC20S-2 39.75 x 30.125 x 24.25 Min. Battery Wt. - 2403 lbs.	36	18-D85-25	35.62	1020	85	6030	38.1875	29.1875	22.6875	2924		X	B	18	SB6320
	36	18-H80-25	33.52	960	80	6030	38.1875	29.1875	22.6875	2807		X	B	18	SB6320
	36	18-P95-25	39.81	1140	95	6030	38.1875	29.1875	22.6875	2953		X	B	18	SB6320

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.	
			KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)		
BC20S-2 39.75 x 30.125 x 24.25 Min. Battery Wt. - 2403 lbs.	48	24-D85-19	35.62	765	85	7003	38.1875	29.6875	22.6875	2994		X	B	18	SB6320	
	48	24-H80-19	33.52	720	80	7003	38.1875	29.6875	22.6875	2874		X	B	18	SB6320	
	48	24-P95-19	39.81	855	95	7003	38.1875	29.6875	22.6875	3024		X	B	18	SB6320	
BC25S-2 39.75 x 30.5625 x 23.1875 Min. Battery Wt. - 2954 lbs.	36	18-D85-25	sp	35.62	1020	85	6745	38.1875	29.1875	22.9375	3025		X	B	18	SB6320
	36	18-D85-25		35.62	1020	85	6030	38.1875	29.1875	22.6875	2924**		X	B	18	SB6320
	36	18-H80-25	sp	33.52	960	80	6745	38.1875	29.1875	22.9375	2904		X	B	18	SB6320
	36	18-H80-25		33.52	960	80	6030	38.1875	29.1875	22.6875	2807**		X	B	18	SB6320
	36	18-P95-25	sp	39.81	1140	95	6745	38.1875	29.1875	22.9375	3055		X	B	18	SB6320
	36	18-P95-25		39.81	1140	95	6030	38.1875	29.1875	22.6875	2953**		X	B	18	SB6320
BC25S-2 39.75 x 30.5625 x 23.1875 Min. Battery Wt. - 2954 lbs.	48	24-D85-19		35.62	765	85	7003	38.1875	29.6875	22.6875	2994		X	B	18	SB6320
	48	24-H80-19		33.52	720	80	7003	38.1875	29.6875	22.6875	2874		X	B	18	SB6320
	48	24-P95-19		39.81	855	95	7003	38.1875	29.6875	22.6875	3024		X	B	18	SB6320
BC25SE-2 39.75 x 34.125 x 24.25 Min. Battery Wt. - 2954 lbs.	36	18-D85-29		41.55	1190	85	6021	38.1875	33.6875	22.6875	3394		X	B	18	SB6320
	36	18-H80-29		39.11	1120	80	6021	38.1875	33.6875	22.6875	3258		X	B	18	SB6320
	36	18-P95-29		46.44	1330	95	6021	38.1875	33.6875	22.6875	3428		X	B	18	SB6320
BC25SE-2 39.75 x 34.125 x 24.25 Min. Battery Wt. - 2954 lbs.	48	24-D85-21		39.58	850	85	7004	38.1875	32.6875	22.6875	3279		X	B	18	SB6320
	48	24-H80-21		37.25	800	80	7004	38.1875	32.6875	22.6875	3148		X	B	18	SB6320
	48	24-P95-21		44.23	950	95	7004	38.1875	32.6875	22.6875	3312		X	B	18	SB6320
BC30S-2 39.75 x 34.125 x 24.25 Min. Battery Wt. - 3572 lbs.	36	18-D85-29		41.55	1190	85	6021	38.1875	33.6875	22.6875	3394**		X	B	18	SB6320
	36	18-H80-29		39.11	1120	80	6021	38.1875	33.6875	22.6875	3258**		X	B	18	SB6320
	36	18-P95-29		46.44	1330	95	6021	38.1875	33.6875	22.6875	3428**		X	B	18	SB6320
BC30S-2 39.75 x 34.125 x 24.25 Min. Battery Wt. - 3572 lbs.	48	24-D85-21		39.58	850	85	7004	38.1875	32.6875	22.6875	3279**		X	B	18	SB6320
	48	24-H80-21		37.25	800	80	7004	38.1875	32.6875	22.6875	3148**		X	B	18	SB6320
	48	24-P95-21		44.23	950	95	7004	38.1875	32.6875	22.6875	3312**		X	B	18	SB6320
BC15T-2, BC15T 38.875 x 20.875 x 25.5625 Min. Battery Wt. - 1936 lbs.	36	18-D85-17		23.75	680	85	6015	38.1875	20.0625	22.6875	2045		X	B	18	SB6320
	36	18-H80-17		22.35	640	80	6015	38.1875	20.0625	22.6875	1963		X	B	18	SB6320
	36	18-P95-17		26.54	760	95	6015	38.1875	20.0625	22.6875	2065		X	B	18	SB6320
BC15T 38.875 x 20.875 x 25.5625 Min. Battery Wt. - 1936 lbs.	48	24-D85-13		23.75	510	85	7017	37.8125	20.5625	22.6875	2038		X	B	18	SB6320
	48	24-H80-13		22.35	480	80	7017	37.8125	20.5625	22.6875	1956		X	B	18	SB6320
	48	24-P95-13		26.54	570	95	7017	37.8125	20.5625	22.6875	2058		X	B	18	SB6320

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
BC18T-2, BC18T 38.875 x 25.0625 x 25.5625 Min. Battery Wt. - 2167 lbs.	36	18-D85-21	29.68	850	85	6010	38.1875	24.5625	22.6875	2466		X	B	18	SB6320
	36	18-H80-21	27.94	800	80	6010	38.1875	24.5625	22.6875	2367		X	B	18	SB6320
	36	18-P95-21	33.17	950	95	6010	38.1875	24.5625	22.6875	2491		X	B	18	SB6320
BC18T 38.875 x 25.0625 x 25.5625 Min. Battery Wt. - 2167 lbs.	48	24-D85-15	27.70	595	85	7031	38.1875	23.5625	22.6875	2325		X	B	18	SB6320
	48	24-H80-15	26.07	560	80	7031	38.1875	23.5625	22.6875	2232		X	B	18	SB6320
	48	24-P95-15	30.96	665	95	7031	38.1875	23.5625	22.6875	2348		X	B	18	SB6320
BC20T-2, BC20T 38.875 x 25.0625 x 25.5625 Min. Battery Wt. - 2398 lbs.	36	18-D85-21	29.68	850	85	6010	38.1875	24.5625	22.6875	2466		X	B	18	SB6320
	36	18-H80-21	27.94	800	80	6010	38.1875	24.5625	22.6875	2367		X	B	18	SB6320
	36	18-P95-21	33.17	950	95	6010	38.1875	24.5625	22.6875	2491		X	B	18	SB6320
BC20T 38.875 x 25.0625 x 25.6875 Min. Battery Wt. - 2398 lbs.	48	24-D100-15	32.59	700	100	7135	38.1875	23.5625	25.6875	2670		X	B	18	SB6320
	48	24-D85-15	27.70	595	85	7031	38.1875	23.5625	22.6875	2325**		X	B	18	SB6320
	48	24-H80-15	26.07	560	80	7031	38.1875	23.5625	22.6875	2232**		X	B	18	SB6320
	48	24-P95-15	30.96	665	95	7031	38.1875	23.5625	22.6875	2348**		X	B	18	SB6320
BC15S, BC15SC, BC18S BC18SC, BC20SC 35.8125 x 27.5 x 24.4375 Min. Battery Wt. - 1850 lbs.	36	18-D85-19	26.71	765	85	6226	34.9375	25.5625	22.6875	2274		X	B	24	SB6320
	36	18-H80-19	25.14	720	80	6226	34.9375	25.5625	22.6875	2183		X	B	24	SB6320
	36	18-P95-19	29.86	855	95	6226	34.9375	25.5625	22.6875	2297		X	B	24	SB6320
B15T-2 38.9375 x 20.8125 x 27 Min. Battery Wt. - 1936 lbs.	36	18-D100-17	27.94	800	100	6060	38.1875	20.0625	25.6875	2322		X	B	18	SB6320
B15T-2 38.9375 x 20.8125 x 27 Min. Battery Wt. - 1936 lbs.	48	24-D100-13	27.94	600	100	7106	37.875	20.5625	25.6875	2342		X	B	18	SB6320
B16X, B18X, B20X 38.9375 x 25.125 x 25.625 Min. Battery Wt. - 2310 lbs.	48	24-D85-15	27.70	595	85	7031	38.1875	23.5625	22.6875	2325		X	B	18	SB6320
	48	24-H80-15	26.07	560	80	7031	38.1875	23.5625	22.6875	2232		X	B	18	SB6320
	48	24-P95-15	30.96	665	95	7031	38.1875	23.5625	22.6875	2348		X	B	18	SB6320
B18T-2 38.9375 x 25.125 x 27 Min. Battery Wt. - 2167 lbs.	36	18-D100-21	34.92	1000	100	6067	38.1875	24.5625	25.6875	2805		X	B	18	SB6320
B18T-2 38.9375 x 25.125 x 27 Min. Battery Wt. - 2167 lbs.	48	24-D100-15	32.59	700	100	7135	38.1875	23.5625	25.6875	2670		X	B	18	SB6320

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
B20T-2 38.9375 x 25.125 x 27 Min. Battery Wt. - 2398 lbs.	36	18-D100-21	34.92	1000	100	6067	38.1875	24.5625	25.6875	2805		X	B	18	SB6320
B20T-2 38.9375 x 25.125 x 27 Min. Battery Wt. - 2398 lbs.	48	24-D100-15	32.59	700	100	7135	38.1875	23.5625	25.6875	2670		X	B	18	SB6320
B20S-3 40.75 x 35.25 x 20.8125 Min. Battery Wt. - 2447 lbs.	48	24-D65-21	30.26	650	65	7141	38.1875	32.6875	20.0625	2785		X	B	24	SB6320
B25S-3 40.75 x 35.25 x 20.8125 Min. Battery Wt. - 2690 lbs.	48	24-D65-21	30.26	650	65	7141	38.1875	32.6875	20.0625	2785		X	B	24	SB6320
B30S, B30S-2 49.25 x 45.5 x 20.9375 Min. Battery Wt. - 3350 lbs.	36 36	18-D65-33 18-D65-33	36.32 36.32	1040 1040	65 65	6555 6273	40 38.1875	40 38.1875	20.0625 20.0625	3486 3286**		X X	B B	30 30	SB6320 SB6320
B30S-3 41.125 x 40.75 x 20.8125 Min. Battery Wt. - 3175 lbs.	48	24-D65-25	36.32	780	65	7521	38.6875	38.1875	20.0625	3276		X	B	24	SB6320
B15T-5 39.125 x 20.75 x 26.75 Min. Battery Wt. - 1544 lbs.	36	18-D100-17	27.94	800	100	6060	38.1875	20.0625	25.6875	2322		X	A	39	SB6320
B15T-5 39.125 x 20.75 x 26.75 Min. Battery Wt. - 1544 lbs.	48	24-D100-13	27.94	600	100	7106	37.875	20.5625	25.6875	2342		X	A	39	SB6320
B18T-5 39.125 x 25 x 26.75 Min. Battery Wt. - 1764 lbs.	36	18-D100-21	34.92	1000	100	6067	38.1875	24.5625	25.6875	2805		X	A	39	SB6320
B18T-5 39.125 x 25 x 26.75 Min. Battery Wt. - 1764 lbs.	48	24-D100-15	32.59	700	100	7135	38.1875	23.5625	25.6875	2670		X	A	39	SB6320

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos. (in.)		
B20T-5 39.125 x 25 x 26.75 Min. Battery Wt. - 2315 lbs.	36	18-D100-21	34.92	1000	100	6067	38.1875	24.5625	25.6875	2805		X	A	39	SB6320
B20T-5 39.125 x 25 x 26.75 Min. Battery Wt. - 2315 lbs.	48	24-D100-15	32.59	700	100	7135	38.1875	23.5625	25.6875	2670		X	A	39	SB6320

** Must use auxiliary counterweight in compartment. (Counterweights are available from truck manufacturer.)

sp - Special tray IST6745 includes steel added for minimum weight requirement.

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

NEW TRAY REQUIRED - Contact East Penn factory for 80 volt design.

Batteries listed are also available in the Max Power "P" Line which is a 10% increase of ampere hour capacity over the standard "D" Line. Refer to Table #2 of Selector Guide for "D" series to Max Power series cross reference table.

EAST PENN manufacturing co., inc.

Lyon Station, PA 19536-0147 • Phone: 610-682-6361 • Fax: 610-682-4212
www.dekabatteries.com • e-mail: epmmotve@eastpenn-deka.com

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are $\pm 1/16"$. Battery weights may vary $\pm 5\%$. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.