



INDUSTRIAL BATTERIES

JUNGHEINRICH

COUNTER BALANCE 3 WHEEL SIT DOWN

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity 6 Hr. Rate		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
EFG110K 32.6875 x 10.75 x 24.6875	24	12-D85-11	9.89	425	85	3811	31.875	10.75	22.5625	838		X	B	16	EBC160
	24	12-H80-11	9.31	400	80	3811	31.875	10.75	22.5625	804		X	B	16	EBC160
	24	12-P95-11	11.06	475	95	3811	31.875	10.75	22.5625	846		X	B	16	EBC160
EFG110 32.6875 x 12.875 x 24.6875	24	12-D85-13	11.87	510	85	3082	30.5625	12.75	22.625	1025		X	B	16	EBC160
	24	12-H80-13	11.17	480	80	3082	30.5625	12.75	22.625	984		X	B	16	EBC160
	24	12-P95-13	13.27	570	95	3082	30.5625	12.75	22.625	1035		X	B	16	EBC160
EFG113 32.6875 x 17.125 x 24.6875	24	12-D85-13	11.87	510	85	3812	30.5625	14.3125	22.625	1272		X	B	16	EBC160
	24	12-H80-13	11.17	480	80	3812	30.5625	14.3125	22.625	1221		X	B	16	EBC160
	24	12-P95-13	13.27	570	95	3812	30.5625	14.3125	22.625	1285		X	B	16	EBC160
EFG115 32.6875 x 19.25 x 24.6875	24	12-D85-21	19.79	850	85	3078	32.5625	19.1875	22.625	1638		X	B	16	EBC160
	24	12-H80-21	18.62	800	80	3078	32.5625	19.1875	22.625	1572		X	B	16	EBC160
	24	12-P95-21	22.12	950	95	3078	32.5625	19.1875	22.625	1654		X	B	16	EBC160
EFG213, EFG215 32.6875 x 20.5625 x 24.6875	48	24-D85-9	15.83	340	85	7651	31.5	19.5	22.625	1489		X	A	16	EBC320
	48	24-H80-9	14.90	320	80	7651	31.5	19.5	22.625	1429		X	A	16	EBC320
	48	24-P95-9	17.69	380	95	7651	31.5	19.5	22.625	1504		X	A	16	EBC320
EFG216K, EFG218K 32.6875 x 24.8125 x 24.6875	48	24-D85-11	19.79	425	85	7444	31.5	22.3125	22.625	1821		X	A	16	EBC320
	48	24-H80-11	18.62	400	80	7444	31.5	22.3125	22.625	1748		X	A	16	EBC320
	48	24-P95-11	22.12	475	95	7444	31.5	22.3125	22.625	1839		X	A	16	EBC320
EFG216, EFG218, EFG220 32.6875 x 29.0625 x 24.6875	48	24-D85-13	23.75	510	85	7442	32	27.75	22.6875	2224		X	A	16	EBC320
	48	24-H80-13	22.35	480	80	7442	32	27.75	22.6875	2135		X	A	16	EBC320
	48	24-P95-13	26.54	570	95	7442	32	27.75	22.6875	2246		X	A	16	EBC320

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

COUNTER BALANCE 4 WHEEL SIT DOWN

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Length Pos. (in.)		
EFG316K, EFG318K 32.6875 x 24.8125 x 24.6875	48	24-D85-11	19.79	425	85	7444	31.5	22.3125	22.625	1821		X	A	16	EBC320
	48	24-H80-11	18.62	400	80	7444	31.5	22.3125	22.625	1748		X	A	16	EBC320
	48	24-P95-11	22.12	475	95	7444	31.5	22.3125	22.625	1839		X	A	16	EBC320
EFG316, EFG318, EFG320 32.6875 x 29.0625 x 24.6875	48	24-D85-13	23.75	510	85	7442	32	27.75	22.6875	2224		X	A	16	EBC320
	48	24-H80-13	22.35	480	80	7442	32	27.75	22.6875	2135		X	A	16	EBC320
	48	24-P95-13	26.54	570	95	7442	32	27.75	22.6875	2246		X	A	16	EBC320
EFG425K, EFG425KS 40.5 x 27.9375 x 30.875	80	40-D125-9	38.80	500	125	9185	39.75	26.75	30.5625	3447		X	A	16	EBC320
	80	40-H120-9	37.25	480	120	9185	39.75	26.75	30.5625	3413		X	A	16	EBC320
	80	40-P140-9	43.46	560	140	9185	39.75	26.75	30.5625	3481		X	A	16	EBC320
EFG425, EFG425S, EFG430 EFG535 40.5 x 33.6875 x 30.875	80	40-D125-11	48.50	625	125	9203	39.5	33	30.5625	4107		X	A	16	EBC320
	80	40-H120-11	46.56	600	120	9203	39.5	33	30.5625	4066		X	A	16	EBC320
	80	40-P140-11	54.32	700	140	9203	39.5	33	30.5625	4148		X	A	16	EBC320
EFG540, EFG545, EFG550 40.5 x 39.375 x 30.875	80	40-D125-13	58.20	750	125	9208	40	39	30.75	4884		X	A	16	EBC320
	80	40-H120-13	55.87	720	120	9208	40	39	30.75	4835		X	A	16	EBC320
	80	40-P140-13	65.18	840	140	9208	40	39	30.75	4933		X	A	16	EBC320
EFG D30 40.4375 x 39.25 x 21.1875	80	40-D65-13	30.26	390	65	9285	39	38.1875	20.0625	3257		X	A	16	EBC320

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

Batteries listed are also available in the Max Power "P" Line which is a 10% increase of ampere hour capacity over the standard "D" Line. Refer to Table #2 of Selector Guide for "D" series to Max Power series cross reference table.

EAST PENN manufacturing co., inc.

Lyon Station, PA 19536-0147 • Phone: 610-682-6361 • Fax: 610-682-4212
www.dekabatteries.com • e-mail: epmmotve@eastpenn-deka.com

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.