









# SPACESAVER™ SYSTEMS AVR95 DISCHARGE RATES *IN AMPS* (cont.)

Ratings in Amperes at 77°F (25°C) to 1.94 v.p.c.

| Cell Type | 1 Min | 5 Min | 10 Min | 15 Min | 20 Min | 30 Min | 1 Hr | 1.5 Hr | 2 Hr | 3 Hr | 4 Hr | 5 Hr | 6 Hr | 7 Hr | 8 Hr | 9 Hr | 10 Hr | 12 Hr | 16 Hr | 20 Hr | 24 Hr | 48 Hr | 72 Hr | 100 Hr |
|-----------|-------|-------|--------|--------|--------|--------|------|--------|------|------|------|------|------|------|------|------|-------|-------|-------|-------|-------|-------|-------|--------|
| AVR95-7   | NA    | NA    | NA     | NA     | NA     | NA     | 99.3 | 82.9   | 71.7 | 56.7 | 47.3 | 40.7 | 35.9 | 32.2 | 29.2 | 26.8 | 24.7  | 21.5  | 17.2  | 14.3  | 12.2  | 6.7   | 4.6   | 3.4    |
| AVR95-9   | NA    | NA    | NA     | NA     | NA     | NA     | 132  | 111    | 95.6 | 75.6 | 63.1 | 54.3 | 47.9 | 42.9 | 39.0 | 35.7 | 33.0  | 28.7  | 22.9  | 19.0  | 16.3  | 8.9   | 6.2   | 4.5    |
| AVR95-11  | NA    | NA    | NA     | NA     | NA     | NA     | 165  | 138    | 119  | 94.6 | 78.8 | 67.9 | 59.9 | 53.7 | 48.7 | 44.7 | 41.2  | 35.9  | 28.6  | 23.8  | 20.4  | 11.2  | 7.7   | 5.7    |
| AVR95-13  | NA    | NA    | NA     | NA     | NA     | NA     | 199  | 166    | 143  | 113  | 94.6 | 81.5 | 71.9 | 64.4 | 58.5 | 53.6 | 49.5  | 43.0  | 34.3  | 28.5  | 24.5  | 13.4  | 9.2   | 6.8    |
| AVR95-15  | NA    | NA    | NA     | NA     | NA     | NA     | 232  | 194    | 167  | 132  | 110  | 95.0 | 83.9 | 75.2 | 68.2 | 62.5 | 57.7  | 50.2  | 40.0  | 33.3  | 28.6  | 15.6  | 10.8  | 7.9    |
| AVR95-17  | NA    | NA    | NA     | NA     | NA     | NA     | 265  | 221    | 191  | 151  | 126  | 109  | 95.9 | 85.9 | 77.9 | 71.5 | 66.0  | 57.4  | 45.7  | 38.0  | 32.6  | 17.9  | 12.3  | 9.0    |
| AVR95-19  | NA    | NA    | NA     | NA     | NA     | NA     | 298  | 249    | 215  | 170  | 142  | 122  | 108  | 96.6 | 87.7 | 80.4 | 74.2  | 64.6  | 51.5  | 42.8  | 36.7  | 20.1  | 13.9  | 10.2   |
| AVR95-21  | NA    | NA    | NA     | NA     | NA     | NA     | 331  | 276    | 239  | 189  | 158  | 136  | 120  | 107  | 97.4 | 89.3 | 82.5  | 71.7  | 57.2  | 47.5  | 40.8  | 22.3  | 15.4  | 11.3   |
| AVR95-23  | NA    | NA    | NA     | NA     | NA     | NA     | 364  | 304    | 263  | 208  | 173  | 149  | 132  | 118  | 107  | 98.3 | 90.7  | 78.9  | 62.9  | 52.3  | 44.9  | 24.6  | 16.9  | 12.4   |
| AVR95-25  | NA    | NA    | NA     | NA     | NA     | NA     | 397  | 332    | 287  | 227  | 189  | 163  | 144  | 129  | 117  | 107  | 99.0  | 86.1  | 68.6  | 57.0  | 48.9  | 26.8  | 18.5  | 13.6   |
| AVR95-27  | NA    | NA    | NA     | NA     | NA     | NA     | 430  | 359    | 311  | 246  | 205  | 177  | 156  | 140  | 127  | 116  | 107   | 93.2  | 74.3  | 61.8  | 53.0  | 29.0  | 20.0  | 14.7   |
| AVR95-29  | NA    | NA    | NA     | NA     | NA     | NA     | 463  | 387    | 335  | 265  | 221  | 190  | 168  | 150  | 136  | 125  | 115   | 100   | 80.0  | 66.5  | 57.1  | 31.3  | 21.6  | 15.8   |
| AVR95-31  | NA    | NA    | NA     | NA     | NA     | NA     | 496  | 415    | 358  | 284  | 237  | 204  | 180  | 161  | 146  | 134  | 124   | 108   | 85.8  | 71.3  | 61.2  | 33.5  | 23.1  | 17.0   |
| AVR95-33  | NA    | NA    | NA     | NA     | NA     | NA     | 529  | 442    | 382  | 303  | 252  | 217  | 192  | 172  | 156  | 143  | 132   | 115   | 91.5  | 76.0  | 65.3  | 35.7  | 24.7  | 18.1   |

## ***EAST PENN manufacturing co., inc.***

Lyon Station, PA 19536-0147 Phone: 610-682-6361 Fax: 610-682-4781

**Order Department Hotline: 610-682-4231**

www.eastpennunigy.com

e-mail: sales@eastpennunigy.com

E.P.M. Form No. 0975B Rev. 6/09  
© 2009 by EPM Printed in U.S.A.

DISTRIBUTED BY:

No part of this document may be copied or reproduced, electronically or mechanically, without written permission from the company.