

ADVANCED **AGM**\* TECHNOLOGY  
\* ABSORBED GLASS MAT

# **Deka** **INTIMIDATOR**

*Superior starting power,  
high reserve capacity  
and long lasting life,  
there's no match for the  
**INTIMIDATOR**  
BATTERY.*

*Advanced AGM  
technology with  
dual purpose design  
makes the **INTIMIDATOR**  
great for quick starts and plenty  
of competition-quality accessory power  
for • stereo systems • boats & RVs  
• hydraulic lifts • winches • on-board  
electronics • and many other power demands.*

*The **INTIMIDATOR'S**  
tight-pack plate and separator construction  
provides added power for resistance against  
hard-hitting stereo, competitive racing or off-road wear and tear vibration.*

*Along with a more efficient design, the **INTIMIDATOR** has the same case/  
cover configuration used by original equipment manufacturers for an easier fit into  
more applications. No elaborate marketing gimmicks or hold-down retrofits,  
just decades of experience to provide a better fit, more power and longer life.*



QUALITY SYSTEM  
CERTIFIED TO  
**ISO 9001**  
**ISO/TS 16949**  
**ISO 14001**

# Deka® INTIMIDATOR®

The INTIMIDATOR is an AGM (absorbed glass mat) dual purpose battery that is completely spillproof and leakproof for your roughest off-road adventures and provides added protection for sophisticated electronic equipment.

**Take a closer look inside the Intimidator's "Cube" Design engineered for high performance and efficiency. Note how active material and plates fill all available space for more power.**



The capability of any battery depends on the weight and formulation of the active materials and the active surface area. Flat plate designs offer more efficiency because they use all of the available volume for active material and headspace (the space above the cells that retain gasses waiting for recombination). The "cube" type design's complete use of internal space allows for a better fit into more applications with less retrofit, while providing maximum power.

## **Additional features of the Intimidator AGM dual purpose battery line:**

- 100% maintenance-free eliminates need to check fluid levels
- Electrolyte absorbed by micro-porous glass separators eliminates acid spills and terminal corrosion
- Tightly "packed" construction and calcium reinforced grids provide greater resistance to shock and vibration
- Faster recharge than conventional batteries allows for faster turnaround times
- Sealed construction provides added protection for sophisticated electronic equipment
- Easy fit and efficient design allows for easy installation in more applications
- Superb dual purpose design delivers great starting and deep cycle service
- Highly porous separators lowers resistance and increases power
- Computer-cast power path grids assures highest quality and optimum performance

GROUP NO.	PART NO. (WET)	PERFORMANCE LEVEL				VOLTS	APPROXIMATE WEIGHT	MAXIMUM OVERALL DIMENSIONS (in inches and mm)						FOOT NOTES
		CCA @ 0°F	RES. CAP.	REF. CA @ 32°F	20 AH RATE			L		W		H		
INTIMIDATOR AGM														
34/78	9A78DT	785	120	970	55	12	42½	10%	273	6%	175	8	203	3,13,16,17
34	9A34	785	120	970	55	12	41	10%	273	6%	175	8	203	3,13,17
34M	9A34M	785	120	970	55	12	41½	10%	273	6%	175	8%	212	3,13,17,U
34R	9A34R	785	120	970	55	12	41	10%	273	6%	175	8	203	3,13,17
31	9A31	925	190	1060	100	12	65	13	330	6%	171	9½	241	3,13,X
	9A31H	925	190	1060	100	12	65	13	330	6%	171	9%	241	3,13,17,X
31P	9A31P	925	190	1060	100	12	65	13	330	6%	171	9%	241	3,13
	9A31PH	925	190	1060	100	12	65	13	330	6%	171	9%	241	3,13,17
65	9A65	800	150	980	75	12	46	12	305	7%	187	7%	194	3,13,17

— All batteries, except PowerSports, have SAE automotive post unless noted

### **FOOTNOTES:**

- 3 - Gold cover / Gray case  
 13 - Absorbed Glass Mat Technology  
 16 - Dual terminal universal design  
 17 - Includes handle

- U - Molded-in offset SAE post and vertical 5/16" NEG., 5/16" POS. stainless steel studs and hex nuts  
 X - 3/8" x 16 stainless steel stud posts

**IMPORTANT CHARGING INSTRUCTIONS:** WARRANTY VOID IF OPENED OR IMPROPERLY CHARGED. Do not install in a sealed container. Constant under- or overcharging will damage any battery and shorten its life! Use a good constant potential, voltage-regulated charger. **Charge to at least 14.4 volts but no more than 14.6 volts at 68°F (20°C).** The **open circuit voltage** of a fully charged 12-volt AGM battery is 12.8V at 68°F (20°C). As the battery charges, the building internal pressure (voltage) causes resistance to the charge. Therefore, the **on-charge voltage** must be higher (at least 14.2V) to overcome this internal pressure (voltage) during charging.

**"POWERED FOR PERFORMANCE"®**

**EAST PENN manufacturing co., inc.**

Lyon Station, PA 19536-0147 • Phone: 610-682-6361 • Fax: 610-682-4781

**Order Department Hotline: 610-682-4231**

www.dekabatteries.com • e-mail: eastpenn@eastpenn-deka.com

E.P.M. Form No. 1143 Rev. 3/11 © 2011 by EPM Printed in U.S.A.

**DISTRIBUTED BY:**

All data subject to change without notice.  
 No part of this document may be copied or reproduced, electronically or mechanically, without written permission from the company.